

DIN EN ISO 20339:2017-08 (E)

Non-destructive testing - Equipment for eddy current examination - Array probe characteristics and verification (ISO 2 0339:2017)

| Contents | | Page |
|--------------------------|---|-------------|
| European foreword | | 4 |
| Foreword | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Probe and interconnecting elements characteristics | 7 |
| 4.1 | General characteristics | 7 |
| 4.1.1 | Application | 7 |
| 4.1.2 | Probe types | 7 |
| 4.1.3 | Interconnecting elements | 7 |
| 4.1.4 | Physical characteristics | 7 |
| 4.1.5 | Safety | 8 |
| 4.1.6 | Environmental conditions | 8 |
| 4.2 | Electrical characteristics | 8 |
| 4.3 | Functional characteristics | 8 |
| 5 | Verification | 9 |
| 5.1 | Level of verifications | 9 |
| 5.2 | Characteristics to be verified | 9 |
| 6 | Measurement of electrical and functional characteristics of an array probe | 10 |
| 6.1 | Electrical characteristics | 10 |
| 6.1.1 | General | 10 |
| 6.1.2 | Measurement conditions | 10 |
| 6.1.3 | Impedance of coil elements | 10 |
| 6.1.4 | Impedance of a pattern | 10 |
| 6.1.5 | Channel assignment — Sequencing | 11 |
| 6.1.6 | Cross-talk | 11 |
| 6.2 | Functional characteristics | 11 |
| 6.2.1 | General | 11 |
| 6.2.2 | Measurement conditions | 11 |
| 7 | Surface array probes | 13 |
| 7.1 | Reference blocks | 13 |
| 7.2 | Probe motion | 14 |
| 7.3 | Reference signal — Normalization | 14 |
| 7.4 | Edge effect (measurable in the case of simple geometry, e.g. metal sheets, disks) | 15 |
| 7.5 | Response to a slot | 16 |
| 7.6 | Response to a hole | 17 |
| 7.7 | Length of coverage | 17 |
| 7.8 | Variation in sensitivity between patterns | 17 |
| 7.9 | Minimum slot length for constant probe response | 18 |
| 7.10 | Lift-off effect | 18 |
| 7.11 | Effect of probe clearance on slot response | 18 |
| 7.12 | Effective depth of detection of a sub-surface slot | 19 |
| 7.13 | Resolution | 19 |
| 7.14 | Defective element or pattern | 19 |

| | | |
|----------|---|-----------|
| 8 | Coaxial array probes | 19 |
| 8.1 | General conditions..... | 19 |
| 8.2 | Reference blocks..... | 19 |
| 8.3 | Reference signal..... | 20 |
| 8.4 | Absence of defective elements..... | 22 |
| 8.5 | Position mark of the probe (mainly for positioning)..... | 22 |
| 8.6 | End effect..... | 22 |
| 8.7 | Length of coverage..... | 22 |
| 8.8 | Homogeneity of axial response..... | 23 |
| 8.9 | Eccentricity effect..... | 24 |
| 8.10 | Fill effect..... | 24 |
| 8.11 | Effective depth of penetration..... | 24 |
| 8.12 | Effective depth of detection under ligament..... | 24 |
| 9 | Influence of interconnecting elements | 24 |
| | Annex A (informative) Simulation of surface probe resolution | 25 |