

DIN ISO 1431-1:2017-04 (E)

Rubber, vulcanized or thermoplastic - Resistance to ozone cracking - Part 1: Static and dynamic strain testing (ISO 143 1-1:2012)

Contents		Page
National foreword		3
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Principle	6
5	Apparatus (see Figure 1)	6
5.1	Test chamber	6
5.2	Source of ozonized air	7
5.3	Means of adjusting the ozone concentration	8
5.4	Means of determining the ozone concentration	8
5.5	Means of adjusting the gas flow	8
5.6	Mounting test pieces for static strain testing	8
5.7	Mounting test pieces for dynamic strain testing	9
6	Calibration	9
7	Test pieces	9
7.1	General	9
7.2	Wide test piece	10
7.3	Narrow test piece	10
8	Conditioning	10
8.1	Conditioning in the unstrained state	10
8.2	Conditioning in the strained state (for static strain testing only)	11
9	Test conditions	11
9.1	Ozone concentration	11
9.2	Temperature	11
9.3	Relative humidity	11
9.4	Maximum elongation	12
10	Static strain testing	12
10.1	General	12
10.2	Procedure A	12
10.3	Procedure B	12
10.4	Procedure C	12
11	Dynamic strain testing	13
11.1	General	13
11.2	Continuous dynamic exposure	13
11.3	Intermittent dynamic exposure	13
12	Expression of results	14
12.1	Procedure A	14
12.2	Procedure B	14
12.3	Procedure C (for static tests only)	14

13	Test report	15
	Annex A (informative) Ozone cracking -- Explanatory notes	17
	Annex B (normative) Calibration schedule	18
	Annex C (informative) Ozone cracking -- Rating scales	20
	Bibliography	21