DIN ISO 1431-1:2017-04 (E)

Rubber, vulcanized or thermoplastic - Resistance to ozone cracking - Part 1: Static and dynamic strain testing (ISO 143 1-1:2012)

Contents

Page

National foreword 3

1 Scope 5

2 Normative references 5

3 Termsanddefinitions 5

4 Principle 6

5 Apparatus (see Figure 1) 6
5.1 Test chamber 6
5.2 Source of ozonized air 7
5.3 Means of adjusting the ozone concentration 8
5.4 Means of determining the ozone concentration 8
5.5 Meansofadjustingthegasflow 8
5.6 Mounting test pieces for static strain testing 8
5.7 Mounting test pieces for dynamic strain testing 9

6 Calibration 9

7 Test pieces 9
7.1 General 9
7.2 Wide test piece 10
7.3 Narrow test piece 10

8 Conditioning 10
8.1 Conditioning in the unstrained state 10
8.2 Conditioning in the strained state (for static strain testing only) 11

9 Test conditions 11
9.1 Ozone concentration 11
9.2 Temperature 11
9.3 Relative humidity 11
9.4 Maximum elongation 12

10 Static strain testing 12
10.1 General 12
10.2 Procedure A 12
10.3 Procedure B 12
10.4 Procedure C 12

11 Dynamic strain testing 13
11.1 General 13
11.2 Continuous dynamic exposure 13
11.3 Intermittent dynamic exposure 13

12 Expression of results 14
12.1 Procedure A 14
12.2 Procedure B 14
12.3 Procedure C (for static tests only) 14

13 Test report 15

Annex A (informative) Ozone cracking -- Explanatory notes 17

Annex B (normative) Calibration schedule 18

Annex C (informative) Ozone cracking -- Rating scales 20

Bibliography 21