

DIN EN ISO 19285:2017-12 (E)

Non-destructive testing of welds - Phased array ultrasonic testing (PAUT) - Acceptance levels (ISO 19285:2017)

| Contents | | Page |
|---|---|-------------|
| European foreword | | 3 |
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Symbols | 5 |
| 5 | Acceptance levels | 6 |
| 6 | Evaluation of indications | 6 |
| 7 | Determination of length and height | 6 |
| 7.1 | General | 6 |
| 7.2 | Determination of length | 6 |
| 7.3 | Determination of height | 6 |
| 7.3.1 | General | 6 |
| 7.3.2 | Using diffracted signals | 6 |
| 7.3.3 | Using other signals | 7 |
| 8 | Determination of length and maximum amplitude | 7 |
| 9 | Acceptance criteria based on length and height | 7 |
| 9.1 | General | 7 |
| 9.2 | Single indications | 7 |
| 9.2.1 | Acceptance criteria for level 1 | 7 |
| 9.2.2 | Acceptance criteria for level 2 | 7 |
| 9.2.3 | Acceptance criteria for level 3 | 8 |
| 9.3 | Cumulative length of indications | 8 |
| 9.3.1 | General | 8 |
| 9.3.2 | For each single set-up | 8 |
| 9.3.3 | Combining set-ups | 9 |
| 9.4 | Grouping of indications | 9 |
| 9.5 | Point-like indications | 10 |
| 10 | Acceptance criteria based on length and amplitude | 10 |
| 10.1 | General | 10 |
| 10.2 | Longitudinal indications | 10 |
| 10.3 | Transverse indications | 10 |
| 10.4 | Grouping of indications | 10 |
| 10.5 | Cumulative length of indications | 11 |
| 10.5.1 | General | 11 |
| 10.5.2 | For each single set-up | 12 |
| 10.5.3 | Combined set-up | 12 |
| Annex A (normative) Levels | | 13 |
| Annex B (normative) Fixed amplitude level technique | | 26 |

| | |
|--|-----------|
| Annex B (normative) Fixed amplitude level technique | 26 |
|--|-----------|