ISO 4662:2017-06 (E)

Rubber, vulcanized or thermoplastic - Determination of rebound resilience

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Principle 2

5 Pendulum method 2
5.1 Apparatus 2
5.1.1 General 2
5.1.2 Oscillatory device 3
5.1.3 System for following the motion of the hammer 3
5.1.4 Test piece holder 3
5.1.5 Temperature control 4
5.1.6 Adjustment of oscillatory device 5
5.2 Test pieces 6
5.2.1 Preparation 6
5.2.2 Dimensions 7
5.2.3 Measurement of dimensions 7
5.2.4 Number of test pieces 7
5.2.5 Time-interval between forming and testing 7
5.2.6 Conditioning 7
5.3 Temperature of test 7
5.4 Procedure 7
5.4.1 Thermal conditioning and mounting of test piece 7
5.4.2 Mechanical conditioning of test piece 8
5.4.3 Measurement of rebound resilience 8
5.4.4 Calculation and expression of results 8
5.5 Precision 8
5.6 Test report 8

6 Tripsometer method 9
6.1 Apparatus 9
6.1.1 General 9
6.1.2 Pendulum 10
6.1.3 System for following the motion of the disc 10
6.1.4 Test piece holder 11
6.1.5 Temperature control 12
6.1.6 Adjustment of oscillatory device 13
6.2 Test pieces 15
6.2.1 Preparation 15
6.2.2 Dimensions 15
6.2.3 Measurement of dimensions 15
6.2.4 Number of test pieces 15
6.2.5 Time-interval between forming and testing 15
6.2.6 Conditioning 15
6.3 Temperature of test 16

6.4 Procedure 16
6.4.1 Thermal conditioning and mounting of test piece 16
6.4.2 Mechanical conditioning of test piece 16
6.4.3 Measurement 16
6.4.4 Calculation and expression of results 16
6.5 Precision 17
6.6 Test report 17

Annex A (informative) Use of non-standard test pieces 18

Annex B (informative) Apparatus designs 21

Annex C (informative) Mounting system for the disc of the tripsometer 22

Annex D (informative) Precision 24

Annex E (informative) Calculation method for the tripsometer's impact velocity 28

Bibliography 31