ISO 2714:2017-11 (E)

Liquid hydrocarbons - Volumetric measurement by displacement meter

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms,definitions,symbolsandabbreviatedterms 1
3.1 Terms and definitions 1
3.2 Symbols and abbreviated terms 5

4 Design and operation of positive displacement meters 5
4.1 Basic characteristics and mode of operation 5
4.2 Reciprocating displacement types 7
4.3 Rotating displacement types 7
4.4 Intermeshing screw spindle type 8
4.5 Oscillating displacement types 9
4.6 Disc type meters 9

5 Performance aspects 9
5.1 General 9
5.2 Factors affecting meter performance 9
5.3 General performance characteristics 9
5.4 Pressure drop and back pressure considerations 11
5.5 Flow profile 11

6 Liquid property effects 11
6.1 General 11
6.2 Effect of viscosity 11
6.3 Effect of temperature 13
6.4 Effect of pressure 13
6.5 Lubricity and liquid cleanliness 14
6.6 Two-phase flow and air elimination 14
6.7 Two-component operation 14
6.8 Pulsating and fluctuating flow 14

7 System design 15
7.1 Design considerations 15
7.2 Selection of displacement meter type 16
7.3 Ancillary equipment 17
7.3.1 General 17
7.3.2 Mechanical accessories 18
7.3.3 Pulse generators and secondary electronic instrumentation 18
7.4 Flow algorithms 19

8 Installation aspects 20
8.1 General 20
8.2 Installation pipework 20
8.3 Flow pulsation 22
8.4 Electrical installation 22
8.5 Pulse security 23

9 Environmental considerations 23
9.1 General 23
9.2 Electrical interference 23
9.3 Humidity 23
9.4 Safety 23

10 Calibration 24
10.1 Proving and verification 24
10.2 General considerations 24
10.3 Proving conditions 24
10.4 Proving methods 24
10.5 Proving frequency 25

11 Operation and maintenance 25
11.1 General 25
11.2 Initial start-up 25
11.3 Meter maintenance 26
11.4 System diagnostics and control charts 26

Annex A (informative)Specificationofperformance 28

Bibliography 35