ISO 16809:2017-11 (E)

Non-destructive testing - Ultrasonic thickness measurement

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Measurement modes 1

5 General requirements 3
5.1 Instruments 3
5.2 Probes 3
5.3 Couplant 3
5.4 Reference blocks 3
5.5 Test objects 3
5.6 Qualification of personnel 4

6 Application of the technique 4
6.1 Surface conditions and surface preparation 4
6.2 Technique 4
6.2.1 General 4
6.2.2 Measurement during manufacture 5
6.2.3 In-service measurement of residual wall thickness 5
6.3 Selection of probe 6
6.4 Selection of instrument 6
6.5 Materials different from the reference material 6
6.6 Special measuring conditions 7
6.6.1 General 7
6.6.2 Measurements at temperatures below 0 °C 7
6.6.3 Measurements at elevated temperatures 7
6.6.4 Hazardous atmospheres 7

7 Instrument setting 7
7.1 General 7
7.2 Methods of setting 8
7.2.1 General 8
7.2.2 Digital thickness instruments 8
7.2.3 A-scan instrument 8
7.3 Checks of settings 9

8 Influenceonaccuracy 10
8.1 Operational conditions 10
8.1.1 Surface conditions 10
8.1.2 Surface temperature 10
8.1.3 Metallic coating 11
8.1.4 Non-metallic coating 11
8.1.5 Geometry 12
8.2 Equipment 12
8.2.1 Resolution 12
8.2.2 Range 13
8.3 Evaluation of accuracy 13

8.3.1 General 13
8.3.2 Influencing parameters 14
8.3.3 Method of calculation 14

9 Influenceofmaterials 14
9.1 General 14
9.2 Inhomogeneity 14
9.3 Anisotropy 14
9.4 Attenuation 14
9.5 Surface conditions 14
9.5.1 General 14
9.5.2 Contact surface 15
9.5.3 Reflecting surface 15
9.5.4 Corrosion and erosion 15

10 Test report 16
10.1 General 16
10.2 General information 16
10.3 Measurement data 17

Annex A (informative) Corrosion in vessels and piping 18

Annex B (informative) Instrument settings 23

Annex C (informative)Parametersinfluencingaccuracy 26

Annex D (informative) Selection of measuring technique 32

Bibliography 37