

ISO 19613:2018 (E)

Fine ceramics (advanced ceramics, advanced technical ceramics) — Measurement of viscosity of ceramic slurry by use of a rotational viscometer

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Principle
4.1	Rotational viscometer with defined shear rate
4.2	Single cylinder viscometer
5	Apparatus
5.1	General
5.2	Rotational viscometer with defined shear rate.
5.2.1	Measuring system
5.2.2	Basic capacity of the instrument
5.2.3	Installation of rotational viscometer
5.2.3.1	Coaxial double cylinder viscometer
5.2.3.2	Cone and plate viscometer
5.3	Single cylinder viscometer.
5.3.1	Main body of single cylinder viscometer
5.3.2	Spindle
5.4	Temperature-control device.
5.4.1	Thermostat
5.4.2	Thermometer
6	Calibration of the rotational viscometer
7	Measurement condition
7.1	Temperature
7.2	Selection of geometry and/or spindle (shear rate or angular velocity)
8	Pretreatment of the sample
8.1	General
8.2	Degassing
8.3	Mixing and dispersion by ultrasonication
9	Measurement procedure
9.1	Sampling
9.2	Measurement at fixed shear rate or angular velocity
9.3	Repeat
10	Expression of the results
11	Test report
Annex A	(informative) Coaxial double cylinder system
A.1	General
A.2	System characteristics
A.3	Standard geometry
A.4	Types of coaxial double cylinder viscometer
A.4.1	Constant velocity outer cylinder system

- A.4.2** Constant velocity inner cylinder system
- A.4.3** Constant torque system

Annex B (informative) Cone and plate system

- B.1** General
- B.2** System characteristics: features and geometry

Annex C (informative) Parallel plate system

- C.1** General
- C.2** System characteristics: features and geometry
- C.3** Notes

Annex D (informative) Single cylinder viscometer

- D.1** General
- D.2** System characteristics: features
- D.3** Standard geometry
- D.4** Measuring principle
- D.5** Notes
- D.5.1** Effect of wall surface of the sample container
- D.5.2** Effect of bottom surface of sample container

Page count: 18