ISO 15029-2:2018 (E)

Petroleum and related products — Determination of spray ignition characteristics of fire-resistant fluids — Part 2: Spray test — Stabilised flame heat release method

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Principle

5 Reagents and materials

6 Apparatus

7 Sampling and sample preparation

8 Apparatus preparation

9 Procedure

- 9.1 Measurements at a propane flow rate of 0,13 Nm3/h
- 9.2 Measurements at a propane flow rate of 0,4 Nm3/h
- 9.3 Rejection of test data
- 9.4 Repeat testing
- 9.5 Number of tests
- 9.5.1 General
- 9.5.2 Calculation
- 9.5.3 Marginal values
- 9.5.4 Conclusion

10 Calculations

- 10.1 Ignitability factor
- 10.1.1 At propane flow rate of 0,13 Nm3/h
- 10.1.2 At propane flow rate of 0,4 Nm3/h
- 10.2 Flame length index
- 10.2.1 At propane flow rate of 0,13 Nm3/h
- 10.2.2 At propane flow rate of 0,4 Nm3/h
- 10.3 Smoke density

11 Expression of results

- 11.1 Individual results
- 11.2 Ranking system

12 Precision

13 Test report

Annex A (normative) Verification of propane pressure and flow rate

- A.1 Apparatus
- A.1.1 Pressure gauge
- A.1.2 Flowmeter
- A.2 Procedure
- A.2.1 Measurement

A.2.2 Verification

Annex B (normative) Verification of propane flame characteristics

B.1 Apparatus
B.1.1 General
B.1.2 Temperature sensor
B.1.3 Traverse system
B.1.4 Insulation board
B.2 Flame temperature measurements
B.2.1 Axial temperatures
B.2.2 Radial temperatures
B.3 Verification
B.3.1 Standard values
B.3.2 Conformity values

Annex C (normative) Test apparatus calibration

C.1 Calibration fluids
C.2 Testing
C.3 Calibration

Annex D (informative) Fire-resistant classification scheme

Annex E (informative) Examples of pro-forma for test results

E.1 General
E.2 Example worksheet for low propane rate results
E.3 Example worksheet for high propane rate results

Page count: 29