

DIN EN ISO 7539-6:2018-12 (E)

Corrosion of metals and alloys - Stress corrosion testing - Part 6: Preparation and use of precracked specimens for tests under constant load or constant displacement (ISO 7539-6:2018)

| Contents | | Page |
|--|---|-----------|
| European foreword | | 3 |
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Principle | 6 |
| 5 | Specimens | 9 |
| 5.1 | General | 9 |
| 5.2 | Specimen design | 11 |
| 5.3 | Stress intensity factor considerations | 21 |
| 5.4 | Specimen preparation | 27 |
| 5.5 | Specimen identification | 29 |
| 6 | Initiation and propagation of fatigue cracks | 30 |
| 7 | Procedure | 31 |
| 7.1 | General | 31 |
| 7.2 | Environmental considerations | 31 |
| 7.3 | Environmental chamber | 32 |
| 7.4 | Environmental control and monitoring | 33 |
| 7.5 | Determination of K_{ISCC} by crack arrest | 33 |
| 7.6 | Determination of K_{ISCC} by crack initiation | 36 |
| 7.7 | Measurement of crack velocity | 38 |
| 8 | Test report | 39 |
| Annex A (informative) Use of notched specimens for stress corrosion tests | | 40 |
| Annex B (informative) Determination of crack growth velocity | | 43 |
| Bibliography | | 44 |