

ISO 21113:2018 (E)

Fine ceramics (advanced ceramics, advanced technical ceramics) — Test method for fracture toughness of monolithic ceramic thin plates at room temperature

Contents

| | |
|---------|--------------------------------------------------------------------|
| | Foreword |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Principle |
| 5 | Apparatus |
| 5.1 | Bend testing machine. |
| 5.2 | Bend test fixture. |
| 6 | Test piece dimension and preparation |
| 6.1 | Shape and dimensions of test piece |
| 6.2 | Test piece preparation |
| 6.3 | Number of test piece |
| 7 | Test methods |
| 7.1 | Three or four-point bending fracture test |
| 7.2 | Measurement of thickness and width of test piece |
| 7.3 | Measurement of precrack length |
| 8 | Evaluation of validity of measured value |
| 9 | Calculation |
| 10 | Test report |
| Annex A | (normative) Test piece preparation for the precracked plate method |
| A.1 | Apparatus |
| A.1.1 | Precracking fixture. |
| A.1.2 | Brass beam. |
| A.1.3 | Wax. |
| A.1.4 | Wax-removing liquid. |
| A.1.5 | Precrack introduction loading apparatus. |
| A.1.6 | Sonic sensor (acoustic emission sensor or stethoscope). |
| A.2 | Introduction of precrack starter |
| A.3 | Introduction of precrack |
| Annex B | (normative) Test piece preparation for the V-notch plate method |
| B.1 | Apparatus |
| B.1.1 | Ordinary razor blades. |
| B.1.2 | Notch honing machine. |
| B.1.3 | Metallographic diamond paste. |
| B.1.4 | Lubricant. |
| B.1.5 | Test piece support. |
| B.1.6 | Diamond slitting saw or slitting machine. |
| B.2 | Preparing the V-notch by machine |
| B.3 | Measurements of both notch-root radius and notch depth |
| B.4 | Evaluation of validity of measured value |

Annex C (normative) Measurement of precrack length and evaluation of validity of measured value for the precracked plate method

- C.1 Measurement of precrack length**
- C.2 Evaluation of validity of measured value**
 - C.2.1 Permissible range of inclination of precrack front line**
 - C.2.2 Permissible range of precrack oblique advance**
 - C.2.3 Permissible range of precrack length**

Page count: 21