

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
4.1	Symbols
4.2	Abbreviated terms for specimen identification
5	Apparatus
6	Specimens
6.1	General
6.2	Crack plane orientation
6.3	Starter notch precracking details
6.4	Stress-intensity factor
6.5	Specimen size
6.6	Specimen thickness
6.7	Residual stress
7	Procedure
7.1	Fatigue precracking
7.2	Crack length measurement
7.3	Constant-force-amplitude, K-increasing, test procedure for $da/dN > 10^{-5}$ mm/cycle
7.4	K-decreasing procedure for $da/dN < 10^{-5}$ mm/cycle
8	Crack length measurement
8.1	Resolution
8.2	Interruption
8.3	Static force
8.4	Measurement interval
8.5	Symmetry
8.6	Out-of-plane cracking
8.7	Crack tip bifurcation
8.8	Non-visual crack length measurement
8.9	Visual crack length measurement
9	Calculations
9.1	Crack-front curvature
9.2	Determining the fatigue crack growth rate
9.2.1	General
9.2.2	Secant method
9.2.3	Incremental polynomial method
9.3	Determination of the fatigue crack growth threshold
10	Test report
10.1	General
10.2	Material
10.3	Test specimen

- 10.4 Precracking terminal values
- 10.5 Test conditions
- 10.6 Test analysis
- 10.7 Presentation of results

Annex A (normative) Compact tension (CT) specimen

- A.1 General
- A.2 Specimen size
- A.2.1 Specimen thickness
- A.2.2 Minimum uncracked ligament
- A.3 Grips and fixtures
- A.4 Crack length measurement interval
- A.5 Stress-intensity factor

Annex B (normative) Centre crack tension (CCT) specimen

- B.1 General
- B.2 Specimen size
- B.2.1 Specimen thickness
- B.2.2 Minimum uncracked ligament
- B.3 Grips and fixtures
- B.3.1 General
- B.3.2 Tension-tension testing
- B.3.3 Tension-compression testing
- B.3.4 Alignment of CCT specimen grips
- B.4 Crack length measurement interval
- B.5 Stress intensity factor

Annex C (normative) Single edge notch tension (SENT) specimen

- C.1 General
- C.2 Specimen size
- C.2.1 Specimen thickness
- C.2.2 Minimum uncracked ligament
- C.3 Grips and fixtures
- C.4 Crack length measurement interval
- C.5 Stress-intensity factor

Annex D (normative) Single edge notch bend (SENB) specimens

- D.1 General
- D.2 Specimen size
- D.2.1 Specimen thickness
- D.2.2 Minimum uncracked ligament
- D.3 Grips and fixtures
- D.3.1 Tension-tension testing of SENB specimens
- D.3.2 Tension-compression grips for the SEN B8 specimen
- D.4 Crack length measurement interval
- D.5 Stress-intensity factor
- D.5.1 General
- D.5.2 Single edge notch three-point bend, SEN B3, specimen
- D.5.3 Single edge notch four-point bend, SEN B4, specimen
- D.5.4 Single edge notch eight-point bend, SEN B8, specimen

Annex E (informative) Non-visual crack length measurement methodology — Electric potential difference[9][12][36]

- E.1 General principles
- E.2 Basic methods
- E.2.1 General
- E.2.2 Direct current method
- E.2.3 Alternating current method
- E.2.3.1 General
- E.2.3.2 Low frequency systems
- E.2.3.3 High frequency systems