ISO 48-9:2018 (E)

Rubber, vulcanized or thermoplastic — Determination of hardness — Part 9: Calibration and verification of hardness testers

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Measurands and metrological requirements for calibration and verification

4.1 Environmental conditions
4.2 Metrological requirements

5 Calibration and verification methods

5.1 Requirements to be met by the measuring instruments used for the calibration and verification methods
5.2 Outline of the calibration and verification methods to be used
5.2.1 Indentors
5.2.1.1 General
5.2.1.2 Type A durometer
5.2.1.3 Type D durometer
5.2.1.4 Type AO durometer
5.2.1.5 Type AM durometer
5.2.1.6 IRHD dead-load methods N, H, L and M and IRHD pocket meter
5.2.1.7 VLRH dead-load meter
5.2.2 Geometry of the pressure foot
5.2.2.1 Diameter/length of side of the pressure foot
5.2.2.2 Hole diameter of the pressure foot
5.2.3 Depth of indentation
5.2.3.1 Type A durometer
5.2.3.2 Type D durometer
5.2.3.3 Type AO durometer
5.2.3.4 Type AM durometer
5.2.3.5 IRHD dead-load method N
5.2.3.6 IRHD dead-load method H
5.2.3.7 IRHD dead-load method L
5.2.3.8 IRHD dead-load method M
5.2.3.9 IRHD pocket meter
5.2.3.10 VLRH dead-load meter
5.2.4 Contact force of the pressure foot
5.2.4.1 Durometers
5.2.4.2 IRHD dead-load methods N, H and L
5.2.4.3 IRHD dead-load method M
5.2.4.4 VLRH dead-load meter
5.2.5 Spring force
5.2.5.1 Type A durometer
5.2.5.2 Type D durometer
5.2.5.3 Type AO durometer
5.2.5.4 Type AM durometer
5.2.5.5 IRHD pocket meter
5.2.6 Contact and total force of IRHD dead-load instruments
5.2.6.1 IRHD dead-load methods N, H and L

5.2.6.2 IRHD dead-load method M
5.2.6.3 VLRH dead-load method
5.2.7 Duration of force application

6 Calibration and verification certificate

Page count: 20