

ISO 17167:2018 (E)

Fine ceramics (advanced ceramics, advanced technical ceramics) — Mechanical properties of monolithic ceramics at room temperature — Determination of flexural strength by the ring-on-ring test

Contents

| | |
|---------|---|
| | Foreword |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Principle |
| 5 | Significance and use |
| 6 | Apparatus |
| 6.1 | Test machine |
| 6.2 | Test jig |
| 6.3 | Calliper or alternative calibrated device for the measurement of the test piece thickness |
| 6.4 | Device for measuring the temperature and humidity |
| 7 | Test pieces |
| 7.1 | General |
| 7.2 | Dimensions and tolerances |
| 7.3 | Surface finish |
| 7.3.1 | General |
| 7.3.2 | Surface finishing I: as-fired |
| 7.3.3 | Surface finishing II: grinding/lapping/polishing |
| 7.3.4 | Surface finish III: finishing by agreed procedure |
| 7.3.5 | Check of dimensions |
| 7.3.6 | General requirements |
| 7.3.7 | Number of test pieces |
| 7.4 | Precautions |
| 8 | Procedure |
| 9 | Calculations |
| 10 | Test report |
| Annex A | (informative) Typical fracture patterns of ceramic test pieces after a ring-on-ring test |