

DIN 51007:2019-04 (E)

Thermal analysis - Differential thermal analysis (DTA) and differential scanning calorimetry (DSC) - General Principles

Contents	Page
Figures Figure 1 -- Endothermic peak -- Characteristic temperatures or times and types of baseline construction upon heating involving a first order phase transition	10
Figure 2 -- Exothermic peak -- Characteristic temperatures or times and types of baseline construction upon cooling involving a first order phase transition	11
Figure 3 -- Endothermic peak -- Construction of a baseline with a point of inflection (type 2)	12
Figure 4 -- Characteristic temperatures and types of baselines for an exothermic peak of a chemical reaction	13
Figure 5 -- DSC curve of a specimen with glass transition	14
Figure 6 -- Determination of the glass transition temperature Tg based on the function $H = H(T)$ of a glass transition with enthalpy relaxation	15
Figure 7 -- Determination of the glass transition temperature Tg based on the heat capacity function $C_p = C_p(T)$ of a glass transition with enthalpy relaxation	16
Figure 8 -- Determination of the glass transition temperature Tg based on the heat capacity function $C_p = C_p(T)$ of a glass transition without enthalpy relaxation	17
Figure 9 -- Determination of heat capacity using two DSC measurements	18
Figure 10 -- VAN'T HOFF plot for determination of the eutectic purity (example)	24
Tables Table 1 -- Typical temperature ranges	7
Table 2 -- Examples of calibration materials	20
Table 3 -- Specific heat capacity cp of synthetic corundum (-Al ₂ O ₃ , "sapphire") [8] [9]	22
Table 4 -- Polynomial coefficients for calculating the molar heat capacity of corundum (-Al ₂ O ₃ , "sapphire", molar mass M = 101,961 3 g mol ⁻¹) [8] [9]	23