DIN 51007:2019-04 (E)

Thermal analysis - Differential thermal analysis (DTA) and differential scanning calorime try (DSC) - General Principles

Contents

Page

Figures Figure 1 -- Endothermic peak -- Characteristic temperatures or times and types of baseline construction upon heating involving a first order phase transition 10

Figure 2 -- Exothermic peak -- Characteristic temperatures or times and types of baseline construction upon cooling involving a first order phase transition 11

Figure 3 -- Endothermic peak -- Construction of a baseline with a point of inflection (type 2) 12

Figure 4 -- Characteristic temperatures and types of baselines for an exothermic peak of a chemical reaction 13

Figure 5 -- DSC curve of a specimen with glass transition 14

Figure 6 -- Determination of the glass transition temperature Tg based on the function H = H (T) of a glass transition with enthalpy relaxation 15

Figure 7 -- Determination of the glass transition temperature Tg based on the heat capacity function Cp = Cp (T) of a glass transition with enthalpy relaxation 16

Figure 8 -- Determination of the glass transition temperature Tg based on the heat capacity function Cp = Cp (T) of a glass transition without enthalpy relaxation 17

Figure 9 -- Determination of heat capacity using two DSC measurements 18

Figure 10 -- VAN'T HOFF plot for determination of the eutectic purity (example) 24

Tables Table 1 -- Typical temperature ranges 7

Table 2 -- Examples of calibration materials 20

Table 3 -- Specific heat capacity cp of synthetic corundum (-Al2O3, "sapphire") [8] [9] 22

Table 4 -- Polynomial coefficients for calculating the molar heat capacity of corundum (-Al2O3, "sapphire", molar mass M = 101,961 3 g mol-1) [8] [9] 23