

DIN EN ISO 28763:2019-12 (E)

Vitreous and porcelain enamels - Regenerative, enamelled and packed panels for air-gas and gas-gas heat exchangers - Specifications (ISO 28763:2019)

| Contents | | Page |
|---|--|-------------|
| European foreword | | 3 |
| Foreword | | 4 |
| 1 Scope | | 5 |
| 2 Normative references | | 5 |
| 3 Terms and definitions | | 5 |
| 4 Steel substrates | | 6 |
| 4.1 Delivery..... | | 6 |
| 4.2 Analysis..... | | 6 |
| 4.3 Hydrogen permeability..... | | 6 |
| 4.4 Fish scaling test..... | | 6 |
| 4.5 Pickling speed..... | | 7 |
| 5 Enamel frit | | 7 |
| 5.1 Delivery..... | | 7 |
| 5.2 Coefficient of expansion..... | | 7 |
| 5.3 Fusion flow..... | | 7 |
| 5.4 Boiling-water (vapour phase) resistance..... | | 7 |
| 5.5 Acid resistance..... | | 7 |
| 5.6 Thermal-shock resistance..... | | 8 |
| 5.7 Adherence..... | | 8 |
| 6 Characteristics of the enamel coating | | 8 |
| 6.1 Adherence..... | | 8 |
| 6.2 Thickness..... | | 8 |
| 6.3 Thermal-shock resistance..... | | 9 |
| 6.4 Fundamental defects..... | | 9 |
| 6.5 Open defects..... | | 9 |
| 6.6 Edge covering of gas-gas heaters..... | | 10 |
| 6.7 Boiling sulfuric acid resistance..... | | 10 |
| 6.8 Rework..... | | 10 |
| 7 Characteristics after packing | | 10 |
| 7.1 Packing pressure..... | | 10 |
| 7.2 Visual examination..... | | 10 |
| 7.3 Edge covering of gas-gas heaters..... | | 11 |
| 8 Documentation | | 11 |
| Annex A (normative) Method for determining thermal-shock resistance of vitreous or porcelain enamel coatings | | 12 |