

# DIN EN ISO 28763:2019-12 (E)

## Vitreous and porcelain enamels - Regenerative, enamelled and packed panels for air-gas and gas-gas heat exchangers - Specifications (ISO 28763:2019)

---

<b>Contents</b>		<b>Page</b>
<b>European foreword</b> .....		<b>3</b>
<b>Foreword</b> .....		<b>4</b>
<b>1</b>	<b>Scope</b> .....	<b>5</b>
<b>2</b>	<b>Normative references</b> .....	<b>5</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>5</b>
<b>4</b>	<b>Steel substrates</b> .....	<b>6</b>
4.1	Delivery.....	6
4.2	Analysis.....	6
4.3	Hydrogen permeability.....	6
4.4	Fish scaling test.....	6
4.5	Pickling speed.....	7
<b>5</b>	<b>Enamel frit</b> .....	<b>7</b>
5.1	Delivery.....	7
5.2	Coefficient of expansion.....	7
5.3	Fusion flow.....	7
5.4	Boiling-water (vapour phase) resistance.....	7
5.5	Acid resistance.....	7
5.6	Thermal-shock resistance.....	8
5.7	Adherence.....	8
<b>6</b>	<b>Characteristics of the enamel coating</b> .....	<b>8</b>
6.1	Adherence.....	8
6.2	Thickness.....	8
6.3	Thermal-shock resistance.....	9
6.4	Fundamental defects.....	9
6.5	Open defects.....	9
6.6	Edge covering of gas-gas heaters.....	10
6.7	Boiling sulfuric acid resistance.....	10
6.8	Rework.....	10
<b>7</b>	<b>Characteristics after packing</b> .....	<b>10</b>
7.1	Packing pressure.....	10
7.2	Visual examination.....	10
7.3	Edge covering of gas-gas heaters.....	11
<b>8</b>	<b>Documentation</b> .....	<b>11</b>
<b>Annex A (normative) Method for determining thermal-shock resistance of vitreous or porcelain enamel coatings</b> .....		<b>12</b>