

ISO 22635:2019-07 (E)

Adhesives - Test methods for adhesives for plastic or rubber floor coverings or wall coverings - Determination of dimensional changes after accelerated ageing

| Contents | | Page |
|-----------------|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Principle | 2 |
| 5 | Apparatus and materials | 2 |
| 6 | Preparation of test specimens | 4 |
| 6.1 | Conditioning of fibre cement substrate | 4 |
| 6.2 | Conditioning of test covering | 5 |
| 6.2.1 | Room temperature storage | 5 |
| 6.2.2 | Elevated temperature pre-treatment | 5 |
| 6.3 | Sampling and conditioning of adhesive | 5 |
| 6.4 | Datum points | 5 |
| 6.4.1 | Fixing of gauge positions | 5 |
| 6.4.2 | Edge to edge measurements | 5 |
| 6.5 | Initial measurements of dimensions prior to bonding | 5 |
| 6.6 | Preparation of bonded test specimens | 6 |
| 6.6.1 | Cleaning | 6 |
| 6.6.2 | Application of adhesive | 6 |
| 6.6.3 | Bonding | 6 |
| 7 | Procedure | 6 |
| 7.1 | Preconditioning | 6 |
| 7.2 | Conditioning cycle (accelerated ageing) | 6 |
| 7.3 | Subsequent cycles | 6 |
| 8 | Evaluation and expression of results | 7 |
| 9 | Test report | 7 |