

ISO/TS 25138:2019 (E)

Surface chemical analysis — Analysis of metal oxide films by glow-discharge optical-emission spectrometry

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Principle
5	Apparatus
5.1	Glow-discharge optical-emission spectrometer
5.1.1	General
5.1.2	Selection of spectral lines
5.1.3	Selection of glow-discharge source type
5.1.3.1	Anode size
5.1.3.2	Type of power supply
5.1.3.3	Mode of operation
6	Adjusting the glow-discharge spectrometer system settings
6.1	General
6.2	Setting the parameters of a DC source
6.2.1	Constant applied current and voltage
6.2.1.1	Setting the high voltage of the detectors
6.2.1.2	Adjusting the source parameters
6.2.1.3	Optimizing the crater shape
6.2.2	Constant applied current and pressure
6.2.3	Constant voltage and pressure
6.3	Setting the discharge parameters of an RF source
6.3.1	General
6.3.2	Constant applied voltage and pressure
6.3.3	Constant applied power and DC bias voltage
6.3.4	Constant effective power and RF voltage
6.4	Minimum performance requirements
6.4.1	General
6.4.2	Minimum repeatability
6.4.3	Detection limit
6.4.3.1	General
6.4.3.2	SNR method
6.4.3.3	SBR#RSDB method
7	Sampling
8	Calibration
8.1	General
8.2	Calibration samples
8.2.1	General
8.2.2	Low alloy iron or steel samples
8.2.3	Stainless-steel samples
8.2.4	Nickel alloy samples
8.2.5	Copper alloy samples
8.2.6	Titanium alloy samples
8.2.7	Silicon samples

8.2.8	Aluminium alloy samples
8.2.9	High-oxygen samples
8.2.10	High-carbon samples
8.2.11	High-nitrogen samples
8.2.12	High-hydrogen samples
8.2.13	High-purity copper samples
8.3	Validation samples
8.3.1	General
8.3.2	Hot-rolled low-alloy steel
8.3.3	Oxidized silicon wafers
8.3.4	TiN-coated samples
8.3.5	Anodized Al ₂ O ₃ samples
8.3.6	TiO ₂ -coated samples
8.4	Determination of the sputtering rate of calibration and validation samples
8.5	Emission intensity measurements of calibration samples
8.6	Calculation of calibration formulae
8.7	Validation of the calibration
8.7.1	General
8.7.2	Checking analytical accuracy using bulk reference materials
8.7.3	Checking analytical accuracy using metal oxide reference materials
8.8	Verification and drift correction
9	Analysis of test samples
9.1	Adjusting discharge parameters
9.2	Setting of measuring time and data acquisition rate
9.3	Quantifying depth profiles of test samples
10	Expression of results
10.1	Expression of quantitative depth profile
10.2	Determination of metal oxide mass per unit area
10.3	Determination of the average mass fractions of the elements in the oxide
11	Precision
12	Test report
Annex A	(informative) Calculation of calibration constants and quantitative evaluation of depth profiles
A.1	Symbols
A.1.1	Symbols used generally in this annex
A.1.2	Symbols used in Clauses A.2 and A.6 concerned with relative sputtering rates
A.1.3	Symbols used in Clauses A.3 and A.7 concerned with absolute sputtering rates
A.2	Calculation of calibration constants using relative sputtering rates
A.3	Calculation of calibration constants using absolute sputtering rates
A.4	Correction of elemental intensities and sputtered mass for variations in discharge parameters
A.4.1	General
A.4.2	Correction of elemental intensities based on tabulated constants for discharge parameters
A.4.3	Voltage correction of the emission yield in the calibration function
A.4.4	Correction of sputtering rate for variations in discharge parameters
A.5	Correction of emission yields due to the influence of hydrogen
A.5.1	General
A.5.2	Correction of elemental intensities based on reference hydrogen intensity and tabulated constants
A.5.3	Hydrogen correction of the emission yield in the calibration function
A.6	Calculation of mass fractions and sputtered mass using relative sputtering rates
A.6.1	General
A.6.2	Calculation based on the relative elemental sputtering rate
A.6.3	Calculation based on the mass fractions of the elements
A.7	Calculation of mass fractions and sputtered mass using absolute sputtering rates
A.7.1	General
A.7.2	Calculation based on elemental sputtering rate
A.7.3	Calculation based on mass fractions of the elements
A.8	Calculation of sputtered depth

- A.8.1 General
- A.8.2 Calculation based on constant atomic volume
- A.8.3 Calculation based on averaged density

Annex B (informative) Suggested spectral lines for determination of given elements

Annex C (informative) Examples of oxide density and the corresponding quantity ρO

Annex D (informative) Report on interlaboratory testing of metal oxide films

- D.1 General
- D.2 Description of samples included in the trial
- D.3 Determination of oxide film thickness
 - D.3.1 Results for sample 1 (low-alloy oxidized steel)
 - D.3.2 Results for sample 2 (annealed high-alloy 1650 SM steel)
 - D.3.3 Results for sample 3 (13 RM 19 high-alloy steel)
 - D.3.4 Results for sample 4 (aluminium oxide on low-alloy steel)
 - D.3.5 Results for sample 5 [titanium oxide on 18/8 high-alloy steel (blue)]
 - D.3.6 Results for sample 6 [titanium oxide on 18/8 high-alloy steel (green)]
 - D.3.7 Results for sample 7 (FeCrAl)
 - D.3.8 Results for sample 8 (oxidized Si)
 - D.3.9 Results for sample 9 (anodized aluminium)

Page count: 40