

# DIN 53100:2020-04 (E)

## Metallic coatings - Electroplated coatings of nickel plus chromium and of copper plus nickel plus chromium on plastics materials

---

<b>Contents</b>	<b>Page</b>
Foreword .....	4
Introduction .....	5
1 Scope .....	6
2 Normative references .....	6
3 Terms and definitions.....	6
4 Ordering details.....	7
4.1 Essential information.....	7
4.2 Additional information.....	7
5 Service condition numbers .....	8
6 Designation .....	8
6.1 General .....	8
6.2 Base material.....	8
6.3 Metal intermediate coatings.....	8
6.3.1 General .....	8
6.3.2 Copper and nickel intermediate coatings .....	8
6.4 Metal coatings.....	9
6.4.1 General .....	9
6.4.2 Nickel coatings .....	9
6.4.3 Chromium coatings.....	9
6.5 Examples of designations .....	10
7 Requirements .....	10
7.1 Base material.....	10
7.2 Appearance of the coated component .....	10
7.3 Thickness of copper or nickel intermediate coating .....	11
7.4 Local coating thickness .....	11
7.5 Thermal cycling test.....	11
7.6 Copper accelerated salt spray test (CASS test) .....	11
7.7 Combined thermal cycling test with CASS test.....	12
7.8 STEP Test (Simultaneous Thickness and Electrode Potential determination) .....	12
8 Sampling.....	12
9 Test method .....	12
10 Test report.....	13
Annex A (informative) Service condition numbers .....	14
Annex B (normative) Methods of determining coating thickness .....	15
B.1 General .....	15
B.2 Methods.....	15
B.2.1 Microscopic method .....	15
B.2.2 Coulometric method.....	15
B.2.3 X-ray spectrometric method.....	15

<b>Annex C (normative) Determination of cracks or pores in the chromium coating</b> .....	<b>17</b>
<b>C.1 General</b> .....	<b>17</b>
<b>C.2 Preparation of parts</b> .....	<b>17</b>
<b>C.3 Galvanostatic test (Dubpernell test)</b> .....	<b>18</b>
<b>C.3.1 Composition of the copper electrolyte</b> .....	<b>18</b>
<b>C.3.2 Working conditions</b> .....	<b>18</b>
<b>C.3.3 Procedure</b> .....	<b>18</b>
<b>C.3.4 Evaluation</b> .....	<b>18</b>
<b>C.4 Potentiostatic Dubpernell test [5]</b> .....	<b>18</b>
<b>C.4.1 Composition of the copper electrolyte</b> .....	<b>18</b>
<b>C.4.2 Working conditions</b> .....	<b>18</b>
<b>C.4.3 Procedure</b> .....	<b>19</b>
<b>C.4.4 Evaluation</b> .....	<b>19</b>
<b>C.5 Potentiostatic test (Fuhrmann test)</b> .....	<b>19</b>
<b>C.5.1 Set-up and description of measuring cell</b> .....	<b>19</b>
<b>C.5.2 Composition of the copper electrolyte</b> .....	<b>20</b>
<b>C.5.3 Working conditions</b> .....	<b>20</b>
<b>C.5.4 Procedure</b> .....	<b>20</b>
<b>C.5.5 Evaluation</b> .....	<b>21</b>
<b>C.6 Anodizing test (Fechner test [7])</b> .....	<b>21</b>
<b>C.6.1 General</b> .....	<b>21</b>
<b>C.6.2 Composition of the electrolyte</b> .....	<b>21</b>
<b>C.6.3 Working conditions</b> .....	<b>21</b>
<b>C.6.4 Procedure</b> .....	<b>21</b>
<b>C.6.5 Evaluation</b> .....	<b>22</b>
<b>Annex D (normative) Thermal cycling test</b> .....	<b>23</b>
<b>D.1 General</b> .....	<b>23</b>
<b>D.2 Principle of method</b> .....	<b>23</b>
<b>D.3 Test pieces</b> .....	<b>23</b>
<b>D.3.1 Sampling and number of test pieces</b> .....	<b>23</b>
<b>D.3.2 Storage of test pieces</b> .....	<b>23</b>
<b>D.4 Test apparatus</b> .....	<b>23</b>
<b>D.5 Procedure</b> .....	<b>24</b>
<b>Annex E (normative) Thermal cycling test combined with CASS test</b> .....	<b>25</b>
<b>E.1 Principle of method</b> .....	<b>25</b>
<b>E.2 Procedure</b> .....	<b>25</b>
<b>Annex F (normative) Glacial acetic acid test</b> .....	<b>26</b>
<b>F.1 General</b> .....	<b>26</b>
<b>F.2 Reagents</b> .....	<b>26</b>
<b>F.3 Test apparatus</b> .....	<b>26</b>
<b>F.4 Procedure</b> .....	<b>26</b>
<b>F.5 Evaluation</b> .....	<b>26</b>
<b>Bibliography</b> .....	<b>27</b>

## Figures

<b>Figure C.1 — Schematic set-up of measuring cell</b> .....	<b>20</b>
--	-----------

## Tables

<b>Table 1 — Requirements for double nickel coatings</b> .....	<b>9</b>
<b>Table 2 — Minimum layer thicknesses for coating systems on plastic</b> .....	<b>11</b>
<b>Table 3 — Requirements</b> .....	<b>12</b>
<b>Table D.1 — Service condition numbers and storage temperatures</b> .....	<b>24</b>