DIN 50002-1:2020-03 (E)

Adhesive bondings in electronic applications - Bonding strength on surfaces - Part 1: Tensile test

Contents

Page

Foreword ... 4

Introduction ... 5

1 Scope ... 6

2 Normative references ... 6

3 Terms and definitions ... 6

4 Principle ... 6

5 Test apparatus ... 7
5.1 Tensile member ... 7
5.2 Tensile testing device ... 7
5.3 Pull-off tool ... 8
5.4 Counter holder ... 8

6 Description of test specimen ... 8

7 Test specimen preparation ... 9
7.1 Tests during production or for quality assurance ... 9
7.2 Bondability testing during the product development phase ... 9

8 Procedure ... 9
8.1 Preparation of the adhesive ... 9
8.2 Bonding of tensile members ... 9
8.2.1 General ... 9
8.2.2 Adjusting the adhesive layer thickness ... 10
8.2.3 Method a) ... 10
8.2.4 Method b) ... 10
8.3 Curing the adhesive ... 11
8.4 Conditioning specimens ... 11
8.5 Destructive testing ... 11

9 Evaluation and presentation of results ... 12
9.1 Assessment of breaking pattern ... 12
9.2 Evaluation of pull-off strength ... 12

10 Test report ... 13

Annex A (informative) **Examples of tensile member geometries** ... 14

Bibliography ... 17

Figures

Figure 1 — Examples of tensile members ... 7

Figure 2 — Possibilities for counterholding during the tensile test; left: stiff test specimen with clamping away from the bond; right: test specimen with reduced stiffness and counterholding directly next to the tensile member bond ... 8

Figure 3 — Selection of the surfaces for bonding the tensile members; left: bonding to a replacement surface; right: bonding to the bonding surface defined by the design 8

Figure 4 — Applying the tensile member according to method a) 10

Figure 5 — Applying the tensile member according to method b) 11

Figure A.1 — Tensile member A1 for adhesives with a tear strength of up to 10 MPa (e.g. silicones) 14

Figure A.2 — Tensile member A2 for adhesives with a tear strength of up to 20 MPa (top) and tensile member B for strengths of up to 50 MPa (bottom) 14

Figure A.3 — Tensile member C for adhesives with an increased tear strength and spacers for adjusting the layer thickness; left: side view of the tensile member; right: plan view of the bond area 15

Figure A.4 — Tensile member D1 for adhesives with increased tear strength — diameter 14 mm 15

Figure A.5 — Tensile member D2 for adhesives with increased tear strength — diameter 20 mm 16