

DIN 50002-1:2020-03 (E)

Adhesive bondings in electronic applications - Bonding strength on surfaces - Part 1: Tensile test

| Contents | Page |
|--|-------------|
| Foreword | 4 |
| Introduction | 5 |
| 1 Scope | 6 |
| 2 Normative references | 6 |
| 3 Terms and definitions..... | 6 |
| 4 Principle..... | 6 |
| 5 Test apparatus | 7 |
| 5.1 Tensile member..... | 7 |
| 5.2 Tensile testing device | 7 |
| 5.3 Pull-off tool..... | 8 |
| 5.4 Counter holder | 8 |
| 6 Description of test specimen | 8 |
| 7 Test specimen preparation..... | 9 |
| 7.1 Tests during production or for quality assurance..... | 9 |
| 7.2 Bondability testing during the product development phase | 9 |
| 8 Procedure | 9 |
| 8.1 Preparation of the adhesive..... | 9 |
| 8.2 Bonding of tensile members..... | 9 |
| 8.2.1 General | 9 |
| 8.2.2 Adjusting the adhesive layer thickness..... | 10 |
| 8.2.3 Method a)..... | 10 |
| 8.2.4 Method b)..... | 10 |
| 8.3 Curing the adhesive | 11 |
| 8.4 Conditioning specimens..... | 11 |
| 8.5 Destructive testing..... | 11 |
| 9 Evaluation and presentation of results..... | 12 |
| 9.1 Assessment of breaking pattern..... | 12 |
| 9.2 Evaluation of pull-off strength | 12 |
| 10 Test report..... | 13 |
| Annex A (informative) Examples of tensile member geometries | 14 |
| Bibliography | 17 |

Figures

| | |
|---|---|
| Figure 1 — Examples of tensile members..... | 7 |
| Figure 2 — Possibilities for counterholding during the tensile test; left: stiff test specimen with clamping away from the bond; right: test specimen with reduced stiffness and counterholding directly next to the tensile member bond..... | 8 |

| | |
|---|-----------|
| Figure 3 — Selection of the surfaces for bonding the tensile members; left: bonding to a replacement surface; right: bonding to the bonding surface defined by the design | 8 |
| Figure 4 — Applying the tensile member according to method a) | 10 |
| Figure 5 — Applying the tensile member according to method b) | 11 |
| Figure A.1 — Tensile member A1 for adhesives with a tear strength of up to 10 MPa (e.g. silicones)..... | 14 |
| Figure A.2 — Tensile member A2 for adhesives with a tear strength of up to 20 MPa (top) and tensile member B for strengths of up to 50 MPa (bottom) | 14 |
| Figure A.3 — Tensile member C for adhesives with an increased tear strength and spacers for adjusting the layer thickness; left: side view of the tensile member; right: plan view of the bond area..... | 15 |
| Figure A.4 — Tensile member D1 for adhesives with increased tear strength — diameter 14 mm..... | 15 |
| Figure A.5 — Tensile member D2 for adhesives with increased tear strength — diameter 20 mm..... | 16 |