

# DIN 50002-1:2020-03 (E)

## Adhesive bondings in electronic applications - Bonding strength on surfaces - Part 1: Tensile test

---

<b>Contents</b>	<b>Page</b>
Foreword .....	4
Introduction .....	5
1 Scope .....	6
2 Normative references .....	6
3 Terms and definitions.....	6
4 Principle.....	6
5 Test apparatus .....	7
5.1 Tensile member.....	7
5.2 Tensile testing device .....	7
5.3 Pull-off tool.....	8
5.4 Counter holder .....	8
6 Description of test specimen .....	8
7 Test specimen preparation.....	9
7.1 Tests during production or for quality assurance.....	9
7.2 Bondability testing during the product development phase .....	9
8 Procedure .....	9
8.1 Preparation of the adhesive.....	9
8.2 Bonding of tensile members.....	9
8.2.1 General .....	9
8.2.2 Adjusting the adhesive layer thickness.....	10
8.2.3 Method a).....	10
8.2.4 Method b).....	10
8.3 Curing the adhesive .....	11
8.4 Conditioning specimens.....	11
8.5 Destructive testing.....	11
9 Evaluation and presentation of results.....	12
9.1 Assessment of breaking pattern.....	12
9.2 Evaluation of pull-off strength .....	12
10 Test report.....	13
Annex A (informative) Examples of tensile member geometries .....	14
Bibliography .....	17

## Figures

Figure 1 — Examples of tensile members.....	7
Figure 2 — Possibilities for counterholding during the tensile test; left: stiff test specimen with clamping away from the bond; right: test specimen with reduced stiffness and counterholding directly next to the tensile member bond.....	8

<b>Figure 3 — Selection of the surfaces for bonding the tensile members; left: bonding to a replacement surface; right: bonding to the bonding surface defined by the design .....</b>	<b>8</b>
<b>Figure 4 — Applying the tensile member according to method a) .....</b>	<b>10</b>
<b>Figure 5 — Applying the tensile member according to method b) .....</b>	<b>11</b>
<b>Figure A.1 — Tensile member A1 for adhesives with a tear strength of up to 10 MPa (e. g. silicones).....</b>	<b>14</b>
<b>Figure A.2 — Tensile member A2 for adhesives with a tear strength of up to 20 MPa (top) and tensile member B for strengths of up to 50 MPa (bottom) .....</b>	<b>14</b>
<b>Figure A.3 — Tensile member C for adhesives with an increased tear strength and spacers for adjusting the layer thickness; left: side view of the tensile member; right: plan view of the bond area.....</b>	<b>15</b>
<b>Figure A.4 — Tensile member D1 for adhesives with increased tear strength — diameter 14 mm.....</b>	<b>15</b>
<b>Figure A.5 — Tensile member D2 for adhesives with increased tear strength — diameter 20 mm.....</b>	<b>16</b>