

# DIN EN 15388:2020-05 (E)

## Agglomerated stone - Slabs and cut-to-size products for vanity and kitchen tops

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>4</b>	<b>Requirements .....</b>	<b>6</b>
<b>4.1</b>	<b>Geometric characteristics .....</b>	<b>6</b>
<b>4.1.1</b>	<b>Dimensions .....</b>	<b>6</b>
<b>4.1.2</b>	<b>Tolerances for dimensions for slabs and cut-to-size products .....</b>	<b>6</b>
<b>4.2</b>	<b>Requirements for surface finish .....</b>	<b>7</b>
<b>4.2.1</b>	<b>General .....</b>	<b>7</b>
<b>4.2.2</b>	<b>Requirements for surfaces after surface finishing .....</b>	<b>7</b>
<b>4.2.3</b>	<b>Requirements for the backside .....</b>	<b>8</b>
<b>4.2.4</b>	<b>Requirements for the edges .....</b>	<b>8</b>
<b>5</b>	<b>Characteristics of agglomerated stones for vanity and kitchen tops .....</b>	<b>8</b>
<b>5.1</b>	<b>General .....</b>	<b>8</b>
<b>5.2</b>	<b>Visual appearance .....</b>	<b>8</b>
<b>5.3</b>	<b>Reaction to fire .....</b>	<b>8</b>
<b>5.4</b>	<b>Apparent density and water absorption .....</b>	<b>8</b>
<b>5.5</b>	<b>Flexural tensile strength .....</b>	<b>8</b>
<b>5.6</b>	<b>Thermal shock resistance .....</b>	<b>8</b>
<b>5.7</b>	<b>Impact resistance .....</b>	<b>9</b>
<b>5.8</b>	<b>Chemical resistance .....</b>	<b>9</b>
<b>5.9</b>	<b>Linear thermal expansion coefficient .....</b>	<b>9</b>
<b>6</b>	<b>Contact with food .....</b>	<b>9</b>
<b>7</b>	<b>Marking, labelling and packaging .....</b>	<b>9</b>
<b>8</b>	<b>Verification of constancy of performance during the production .....</b>	<b>10</b>
<b>8.1</b>	<b>General rules .....</b>	<b>10</b>
<b>8.2</b>	<b>Type testing of the agglomerated stone material properties .....</b>	<b>10</b>
<b>8.3</b>	<b>FPC - Tests to be carried out .....</b>	<b>10</b>
<b>Annex A (normative) Reference sample, visual inspection and acceptance criteria .....</b>		<b>12</b>