

# DIN EN 1097-8:2020-06 (E)

## Tests for mechanical and physical properties of aggregates - Part 8: Determination of the polished stone value

---

<b>Contents</b>		<b>Page</b>
<b>European foreword</b> .....		<b>4</b>
<b>1</b>	<b>Scope</b> .....	<b>6</b>
<b>2</b>	<b>Normative references</b> .....	<b>6</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>6</b>
<b>4</b>	<b>Principle</b> .....	<b>7</b>
<b>5</b>	<b>Materials</b> .....	<b>7</b>
<b>5.1</b>	<b>General</b> .....	<b>7</b>
<b>5.2</b>	<b>Materials</b> .....	<b>7</b>
<b>6</b>	<b>Apparatus</b> .....	<b>8</b>
<b>6.1</b>	<b>General</b> .....	<b>8</b>
<b>6.2</b>	<b>Accelerated polishing machine</b> .....	<b>8</b>
<b>6.3</b>	<b>Friction tester</b> .....	<b>11</b>
<b>6.4</b>	<b>Test sieves</b> .....	<b>14</b>
<b>6.5</b>	<b>Grid sieve</b> .....	<b>14</b>
<b>6.6</b>	<b>Length gauge or callipers</b> .....	<b>14</b>
<b>6.7</b>	<b>Equipment for preparing test specimens</b> .....	<b>14</b>
<b>7</b>	<b>Preparation of test specimens</b> .....	<b>15</b>
<b>8</b>	<b>Conditioning of the rubber-tyred wheel</b> .....	<b>16</b>
<b>9</b>	<b>Accelerated polishing of specimens</b> .....	<b>16</b>
<b>10</b>	<b>Friction test procedure</b> .....	<b>18</b>
<b>11</b>	<b>Calculation and expression of results</b> .....	<b>21</b>
<b>12</b>	<b>Test report</b> .....	<b>22</b>
<b>12.1</b>	<b>Required data</b> .....	<b>22</b>
<b>12.2</b>	<b>Optional data</b> .....	<b>22</b>
<b>Annex A(normative) Determination of aggregate abrasion value (AAV)</b> .....		<b>23</b>
<b>A.1</b>	<b>General</b> .....	<b>23</b>
<b>A.2</b>	<b>Principle</b> .....	<b>23</b>
<b>A.3</b>	<b>Materials</b> .....	<b>23</b>
<b>A.4</b>	<b>Apparatus</b> .....	<b>24</b>
<b>A.4.1</b>	<b>General</b> .....	<b>24</b>
<b>A.4.2</b>	<b>Abrasion machine</b> .....	<b>24</b>
<b>A.4.3</b>	<b>Test sieves</b> .....	<b>24</b>
<b>A.4.4</b>	<b>Grid sieve</b> .....	<b>24</b>
<b>A.4.5</b>	<b>Balance</b> .....	<b>25</b>
<b>A.4.6</b>	<b>Small fine-haired brushes</b> .....	<b>25</b>
<b>A.4.7</b>	<b>Brush</b> .....	<b>25</b>
<b>A.4.8</b>	<b>Clamp</b> .....	<b>25</b>

<b>A.5</b>	<b>Preparation of test specimens</b> .....	<b>25</b>
<b>A.5.1</b>	<b>Test portion</b> .....	<b>25</b>
<b>A.5.2</b>	<b>Specimens</b> .....	<b>25</b>
<b>A.6</b>	<b>Procedure</b> .....	<b>25</b>
<b>A.7</b>	<b>Calculation and expression of results</b> .....	<b>26</b>
<b>A.8</b>	<b>Test report</b> .....	<b>26</b>
<b>Annex B(normative) Control of materials - Corn emery and emery flour</b> .....		<b>27</b>
<b>Annex C(normative) Calibration of the accelerated polishing machine</b> .....		<b>28</b>
<b>C.1</b>	<b>Control of rubber-tyred wheels</b> .....	<b>28</b>
<b>C.2</b>	<b>Accelerated polishing machine</b> .....	<b>28</b>
<b>C.3</b>	<b>Rate of flow of corn emery and emery flour</b> .....	<b>30</b>
<b>Annex D(normative) Calibration of the friction tester and sliders</b> .....		<b>31</b>
<b>D.1</b>	<b>Friction tester</b> .....	<b>31</b>
<b>D.1.1</b>	<b>General</b> .....	<b>31</b>
<b>D.1.2</b>	<b>Mass of pendulum arm and pointer</b> .....	<b>31</b>
<b>D.1.3</b>	<b>Balancing of the pendulum arm assembly</b> .....	<b>31</b>
<b>D.1.4</b>	<b>Setting the effective spring tension</b> .....	<b>31</b>
<b>D.1.5</b>	<b>Setting the pointer stop</b> .....	<b>31</b>
<b>D.2</b>	<b>Control of sliders and slider rubber</b> .....	<b>32</b>
<b>Annex E(normative) Friction tester reference stone specimen preparation and friction slider conditioning</b> .....		<b>33</b>
<b>E.1</b>	<b>General</b> .....	<b>33</b>
<b>E.2</b>	<b>Preparation and initial testing of friction tester reference stone specimens</b> .....	<b>33</b>
<b>E.3</b>	<b>Slider conditioning</b> .....	<b>33</b>
<b>Annex F(informative) Precision for the aggregate abrasion value (AAV)</b> .....		<b>34</b>
<b>F.1</b>	<b>General</b> .....	<b>34</b>
<b>F.2</b>	<b>Precision values for repeatability and reproducibility</b> .....	<b>34</b>
<b>Bibliography</b> .....		<b>35</b>