

# ISO 2648:2020-01 (E)

## Wool - Determination of fibre length distribution parameters - Capacitance method

Contents	Page
Foreword	iv
<b>1 Scope</b>	<b>1</b>
<b>2 Normative references</b>	<b>1</b>
<b>3 Terms and definitions</b>	<b>1</b>
<b>4 Principle</b>	<b>2</b>
<b>5 Apparatus</b>	<b>2</b>
<b>6 Conditioning and testing atmosphere</b>	<b>3</b>
6.1 Conditioning atmosphere	3
6.2 Testing atmosphere	4
<b>7 Sampling and preparation of laboratory sample</b>	<b>4</b>
7.1 Sampling	4
7.2 Preparation of laboratory sample	4
7.2.1 General	4
7.2.2 Slivers of combed wool weighing between 15 g/m and 30 g/m	4
7.2.3 Rovings or slivers weighing less than 15 g/m	4
7.2.4 Rovings or slivers weighing more than 30 g/m	5
<b>8 Procedure</b>	<b>5</b>
8.1 Preparation of test specimen	5
8.2 Measurement	5
<b>9 Calculation and expression of results</b>	<b>6</b>
9.1 Analogue system	6
9.1.1 Calculation of Hauteur ( <b>H</b> ) and Barbe ( <b>B</b> )	6
9.1.2 Calculation of coefficient of variation of Hauteur $CV_H$	6
9.1.3 Percentage of short fibres	7
9.1.4 Use of the nomograms	7
9.2 Digital system	7
9.2.1 General	7
9.2.2 Calculation of Hauteur ( <b>H</b> )	7
9.2.3 Calculation of the coefficient of variation of Hauteur, $CV_H$	7
9.2.4 Calculation of Barbe ( <b>B</b> )	8
9.2.5 Calculation of the coefficient of variation of Barbe, $CV_B$	8
9.2.6 Tuft diagram	8
9.2.7 Fibre length attributes (L values and K values)	8
<b>10 Test report</b>	<b>9</b>
<b>11 Precision</b>	<b>9</b>
11.1 Precision of the method	9
11.2 Within and between laboratory variation for Hauteur and Barbe	9
11.3 95 % confidence intervals for Hauteur and Barbe	10
11.4 MPD% values for Hauteur and Barbe based on k measurements	10
<b>Annex A (normative) Preparation of top and sliver</b>	<b>12</b>
<b>Annex B (normative) Test specimen preparation</b>	<b>15</b>
<b>Annex C (informative) Precision of the method</b>	<b>17</b>
<b>Bibliography</b>	<b>21</b>