

ISO 21903:2020-02 (E)

Refrigerated hydrocarbon fluids - Dynamic measurement - Requirements and guidelines for the calibration and installation of flowmeters used for liquefied natural gas (LNG) and other refrigerated hydrocarbon fluids

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions and abbreviated terms | 1 |
| 3.1 | Terms and definitions | 1 |
| 3.2 | Abbreviated terms | 3 |
| 4 | Flowmeter selection | 3 |
| 4.1 | Considerations of meters specific to LNG metering | 3 |
| 4.2 | Coriolis flowmeter | 4 |
| 4.3 | Ultrasonic flowmeter | 4 |
| 5 | Process conditions | 5 |
| 5.1 | Temperature effects | 5 |
| 5.1.1 | Loading procedures | 5 |
| 5.1.2 | Temperature effects on CMF measurements | 5 |
| 5.1.3 | Temperature effects on USM measurements | 6 |
| 5.2 | Pressure effects | 6 |
| 5.2.1 | Coriolis flowmeter | 6 |
| 5.2.2 | Ultrasonic flowmeter | 7 |
| 5.3 | Mechanical vibrations | 7 |
| 5.3.1 | Coriolis flowmeter | 7 |
| 5.3.2 | Ultrasonic flowmeter | 8 |
| 5.4 | Cavitation | 8 |
| 5.4.1 | Coriolis flowmeter | 8 |
| 5.4.2 | Ultrasonic flowmeter | 9 |
| 5.5 | Thermodynamic properties of LNG | 9 |
| 6 | Installation | 9 |
| 6.1 | Valves | 9 |
| 6.2 | Swirl and non-uniform profiles | 9 |
| 6.2.1 | Coriolis flowmeter | 9 |
| 6.2.2 | Ultrasonic flowmeter | 10 |
| 6.3 | Flow conditioners | 10 |
| 6.4 | Pipe stress and torsion | 10 |
| 6.4.1 | Coriolis flowmeter | 10 |
| 6.4.2 | Ultrasonic flowmeter | 11 |
| 6.5 | Flowmeter installation recommendations | 11 |
| 6.5.1 | Coriolis flowmeter | 11 |
| 6.5.2 | Ultrasonic flowmeter | 12 |
| 6.6 | Crosstalk and sensitivity to noise | 12 |
| 6.6.1 | Coriolis flowmeter | 12 |
| 6.6.2 | Ultrasonic flowmeter | 12 |
| 6.7 | Zero offset -- Verification and adjustment procedures | 13 |

| | | |
|--|--|----|
| 6.7.1 | Coriolis flowmeter | 13 |
| 6.7.2 | Ultrasonic flowmeter | 15 |
| 6.8 | Temperature management | 15 |
| 6.8.1 | Thermal insulation | 15 |
| 6.8.2 | Cooling procedure | 16 |
| 6.8.3 | Warming procedure | 17 |
| 7 | Calibration | 18 |
| 7.1 | General considerations | 18 |
| 7.2 | Calibration in a laboratory | 18 |
| 7.2.1 | Gravimetric method | 18 |
| 7.2.2 | Master meter method | 20 |
| 7.3 | Calibration in situ | 22 |
| 7.3.1 | Gravimetric method using a weighbridge | 22 |
| 7.3.2 | Road tanker temporarily on weighbridge | 23 |
| 7.3.3 | Measurement uncertainty | 23 |
| 7.4 | Interconnected pipe volume | 23 |
| Annex A (informative) Working principle Coriolis flowmeter | | 27 |
| Annex B (informative) Working principle of the ultrasonic flowmeter | | 30 |
| Annex C (normative) Hardware for an LNG calibration facility | | 33 |
| Annex D (informative) Examples of calibration data | | 36 |
| Annex E (normative) Alternative calibration procedure based on alternative liquids | | 39 |
| Annex F (informative) Thermodynamic properties of LNG | | 41 |
| Bibliography | | 47 |