

DIN EN ISO 22232-1:2021-09 (E)

Non-destructive testing - Characterization and verification of ultrasonic test equipment - Part 1: Instruments (ISO 22232-1:2020)

| Contents | | Page |
|--------------------------------|--|-------------|
| European foreword | | 4 |
| Foreword | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Symbols | 8 |
| 5 | General requirements of conformity | 9 |
| 6 | Manufacturer's technical specification for ultrasonic instruments | 9 |
| 7 | Performance requirements for ultrasonic instruments | 12 |
| 8 | Group 1 tests | 14 |
| 8.1 | Equipment required for group 1 tests | 14 |
| 8.2 | Battery operational time | 14 |
| | 8.2.1 Procedure | 14 |
| | 8.2.2 Acceptance criterion | 15 |
| 8.3 | Stability after warm-up time | 15 |
| | 8.3.1 Procedure | 15 |
| | 8.3.2 Acceptance criteria | 15 |
| 8.4 | Stability against temperature | 15 |
| | 8.4.1 Procedure | 15 |
| | 8.4.2 Acceptance criterion | 17 |
| 8.5 | Stability against voltage variation | 17 |
| | 8.5.1 Procedure | 17 |
| | 8.5.2 Acceptance criterion | 18 |
| 8.6 | Time base deviation | 18 |
| | 8.6.1 Procedure | 18 |
| | 8.6.2 Acceptance criterion | 20 |
| 8.7 | Transmitter pulse parameters | 20 |
| | 8.7.1 General | 20 |
| | 8.7.2 Pulse repetition frequency | 20 |
| | 8.7.3 Effective output impedance | 20 |
| 8.8 | Receiver | 21 |
| | 8.8.1 General | 21 |
| | 8.8.2 Cross talk from transmitter to receiver during transmission | 21 |
| | 8.8.3 Dead time after transmitter pulse | 22 |
| | 8.8.4 Dynamic range and maximum input voltage | 24 |
| | 8.8.5 Receiver input impedance | 25 |
| | 8.8.6 Time-corrected gain (TCG) | 26 |
| 8.9 | Gates | 27 |
| | 8.9.1 General | 27 |
| | 8.9.2 Gates with value output | 28 |
| | 8.9.3 Gates with analogue output | 30 |
| | 8.9.4 Gates with alarm output | 32 |
| 8.10 | Highest digitized frequency | 33 |
| | 8.10.1 Procedure | 33 |

| | | | |
|----------|--------|---|-----------|
| | 8.10.2 | Acceptance criterion..... | 34 |
| 8.11 | | Response time of digital ultrasonic instruments..... | 34 |
| | 8.11.1 | General..... | 34 |
| | 8.11.2 | Procedure..... | 34 |
| | 8.11.3 | Acceptance criterion..... | 35 |
| 9 | | Group 2 tests..... | 35 |
| 9.1 | | Equipment required for group 2 tests..... | 35 |
| 9.2 | | Physical state and external aspects..... | 36 |
| | 9.2.1 | Procedure..... | 36 |
| | 9.2.2 | Acceptance criterion..... | 36 |
| 9.3 | | Transmitter voltage, pulse rise time and duration..... | 36 |
| | 9.3.1 | Procedure..... | 36 |
| | 9.3.2 | Acceptance criteria..... | 39 |
| 9.4 | | Receiver..... | 39 |
| | 9.4.1 | General..... | 39 |
| | 9.4.2 | Frequency response..... | 39 |
| | 9.4.3 | Noise level..... | 41 |
| | 9.4.4 | Gain linearity..... | 42 |
| | 9.4.5 | Vertical display linearity..... | 42 |
| | | Annex A (normative) Special conditions for ultrasonic instruments with logarithmic amplifiers..... | 44 |
| | | Bibliography..... | 45 |