

# DIN 51629:2020-09 (E)

## Liquefied petroleum gases - Propane, propene, butane, butene and their mixtures with a maximum sulfur content of 50 mg/kg - Requirements

---

### Contents

Page

<b>Foreword .....</b>	<b>3</b>
<b>1 Scope .....</b>	<b>4</b>
<b>2 Normative references .....</b>	<b>5</b>
<b>3 Terms and definitions.....</b>	<b>6</b>
<b>4 Sampling.....</b>	<b>7</b>
<b>5 Requirements and test methods .....</b>	<b>7</b>
<b>5.1 General .....</b>	<b>7</b>
<b>5.2 Odour .....</b>	<b>7</b>
<b>5.3 Precision and cases of dispute .....</b>	<b>8</b>
<b>Annex A (normative) Determining the odour of liquefied petroleum gas .....</b>	<b>9</b>
<b>A.1 General .....</b>	<b>9</b>
<b>A.2 Principle .....</b>	<b>9</b>
<b>A.3 Material .....</b>	<b>9</b>
<b>A.4 Apparatus .....</b>	<b>9</b>
<b>A.5 Procedure .....</b>	<b>11</b>
<b>A.6 Expression of results.....</b>	<b>11</b>
<b>Bibliography .....</b>	<b>12</b>

### Figures

<b>Figure A.1 — Apparatus for assessing the odour of liquefied petroleum gas (LPG) .....</b>	<b>10</b>
--	-----------

### Tables

<b>Table 1 — Requirements and test methods .....</b>	<b>7</b>
--	----------