DIN ISO 18516:2020-11 (E)

Surface chemical analysis - Determination of lateral resolution and sharpness in beam based methods with a range from nanometers to micrometers (ISO 18516:2019); Text in English

Inhalt

Seite

Nationales Vorwort **3**

Nationaler Anhang NA (informativ) Literaturhinweise **4**

Nationaler Anhang NB (informativ) Begriffe **5**

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Symbols and abbreviated terms **3**

5 General information **4**

5.1 Background 4

5.2 Survey on principal methods to characterize lateral resolution in imaging surface chemical analysis 5

5.3 Measurement of lateral resolution in imaging surface chemical analysis 6

5.4 Dependence of lateral resolution on scan direction 6

5.5 Reporting results 7

6 Measurement of lateral resolution using the straight edge method **8**

6.1 Introduction 8

6.2 Model functions and sharpness parameters 8

6.3 Requirements for a test sample 9

6.4 Cleaning the straight-edge specimen 10

6.5 Mounting the straight-edge specimen 10

6.6 Operating the instrument 10

6.7 Data acquisition requirements 10

6.8 Determination of D_{12-88} 11

6.9 Determination of line spread function 11

6.10 Reporting 11

7 Measurement of lateral resolution using the narrow line method **13**

7.1 Introduction 13

7.2 Requirements for a test sample 13

7.3 Cleaning the narrow stripe specimen 13

7.4 Mounting the narrow stripe specimen 14

7.5 Operating the instrument 14

7.6 Data acquisition requirements 14

7.7 Determination of w_{LSF} 14

7.8 Reporting 15

8 Measurement of lateral resolution using the grating method 17
8.1 Introduction 17
8.2 Requirements for a test sample 17
8.3 Cleaning the grating specimen 19
8.4 Mounting the grating specimen 19
8.5 Operating the instrument 20
8.6 Data acquisition 20
8.7 Estimation of effective lateral resolution r_e by visual inspection of an image or a line scan 20
8.8 Determination of effective lateral resolution r_e by numerical analysis of a line profile 23
8.8.1 General 23
8.8.2 Consideration of noise and determination of reduced noise σ_{Nr} 23
8.8.3 Determination of dip D 24
8.8.4 Resolution criterion 25
8.9 Determination of the effective lateral resolution r_e using graded gratings 26
8.9.1 Estimation of effective lateral resolution r_e by using the resolution criterion in Formula (17) 26
8.9.2 Determination of effective lateral resolution r_e by using Formula (17) and an interpolation–extrapolation method 27
8.10 Reporting 29

Annex A (informative) **The relation between sharpness parameters and effective lateral resolution 31**

Annex B (informative) **Straight edge method: systematic underestimation of D_{12-88} caused by insufficient plateau length L_{pl} 33**

Annex C (informative) **Straight edge method: required length ranges for L_{ESF} 35**

Annex D (informative) **Straight edge method: the uncertainty of D_{12-88} 36**

Annex E (informative) **Narrow stripe method: systematic overestimation of w_{LSF} caused by inappropriately large widths w_s of the imaged stripe 37**

Annex F (informative) **Narrow line method: the uncertainty of w_{LSF} 39**

Annex G (informative) **Imaging of square gratings: reduction of image period for three-stripe gratings 40**

Annex H (informative) **Imaging of square gratings: relation between signal-to-noise ratio and effective lateral resolution 43**

Annex I (informative) **Imaging of square gratings: minimum number of sampling points per period 46**

Annex J (informative) **Imaging of square gratings: uncertainty of r_e determined by visual inspection of an image or line scan over a series of gratings 47**

Annex K (informative) **Imaging of square gratings: Uncertainty of r_e determined by interpolation–extrapolation 48**

Annex L (informative) **Determination of lateral resolution by imaging of square wave gratings — practical example for SIMS 50**

Bibliography 53