

DIN EN ISO 22232-2:2021-09 (E)

Non-destructive testing - Characterization and verification of ultrasonic test equipment - Part 2: Probes (ISO 22232-2:2020)

| Contents | | Page |
|--------------------------|---|-------------|
| European foreword | | 4 |
| Foreword | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 6 |
| 4 | Symbols | 8 |
| 5 | General requirements of conformity | 9 |
| 6 | Technical information for probes | 10 |
| 6.1 | General | 10 |
| 6.2 | Probe data sheet | 10 |
| 6.3 | Probe test report | 10 |
| 7 | Test equipment | 12 |
| 7.1 | Electronic equipment | 12 |
| 7.2 | Test blocks and other equipment | 12 |
| 8 | Performance requirements for probes | 20 |
| 8.1 | Physical aspects | 20 |
| 8.1.1 | Procedure | 20 |
| 8.1.2 | Acceptance criterion | 20 |
| 8.2 | Pulse shape, amplitude and duration | 20 |
| 8.2.1 | Procedure | 20 |
| 8.2.2 | Acceptance criterion | 21 |
| 8.3 | Frequency spectrum and bandwidth | 22 |
| 8.3.1 | Procedure | 22 |
| 8.3.2 | Acceptance criteria | 22 |
| 8.4 | Pulse-echo sensitivity | 22 |
| 8.4.1 | Procedure | 22 |
| 8.4.2 | Acceptance criterion | 23 |
| 8.5 | Distance-amplitude curve | 23 |
| 8.5.1 | General | 23 |
| 8.5.2 | Procedure | 23 |
| 8.5.3 | Acceptance criterion | 25 |
| 8.6 | Beam parameters for immersion probes | 25 |
| 8.6.1 | General | 25 |
| 8.6.2 | Beam profile — Measurements performed directly on the beam | 26 |
| 8.6.3 | Beam profile — Measurements made using an automated scanning system | 33 |
| 8.7 | Beam parameters for straight-beam single-transducer contact probes | 35 |
| 8.7.1 | General | 35 |
| 8.7.2 | Beam divergence and side lobes | 36 |
| 8.7.3 | Squint angle and offset for straight-beam probes | 37 |
| 8.7.4 | Focal distance (near field length) | 38 |
| 8.7.5 | Focal width | 38 |
| 8.7.6 | Length of the focal zone | 39 |
| 8.8 | Beam parameters for angle-beam single-transducer contact probes | 39 |
| 8.8.1 | General | 39 |
| 8.8.2 | Index point | 39 |

| | | |
|---|---|-----------|
| 8.8.3 | Beam angle and beam divergence..... | 40 |
| 8.8.4 | Squint angle and offset for angle-beam probes..... | 43 |
| 8.8.5 | Focal distance (near field length)..... | 46 |
| 8.8.6 | Focal width..... | 47 |
| 8.8.7 | Length of the focal zone..... | 47 |
| 8.9 | Beam parameters for straight-beam dual-transducer contact probes..... | 48 |
| 8.9.1 | General..... | 48 |
| 8.9.2 | Delay line delay path..... | 48 |
| 8.9.3 | Focal distance..... | 48 |
| 8.9.4 | Axial sensitivity range (focal zone)..... | 48 |
| 8.9.5 | Lateral sensitivity range (focal width)..... | 49 |
| 8.10 | Beam parameters for angle-beam dual-transducer contact probes..... | 50 |
| 8.10.1 | General..... | 50 |
| 8.10.2 | Index point..... | 50 |
| 8.10.3 | Beam angle and profiles..... | 50 |
| 8.10.4 | Wedge delay path..... | 51 |
| 8.10.5 | Distance to sensitivity maximum (focal distance)..... | 51 |
| 8.10.6 | Axial sensitivity range (length of the focal zone)..... | 51 |
| 8.10.7 | Lateral sensitivity range (focal width)..... | 51 |
| 8.11 | Crosstalk..... | 52 |
| 8.11.1 | Procedure..... | 52 |
| 8.11.2 | Acceptance criterion..... | 52 |
| Annex A (normative) Calculation of the near field length of non-focusing probes..... | | 53 |
| Annex B (informative) Calibration block for angle-beam probes..... | | 56 |
| Annex C (informative) Determination of delay line and wedge delays..... | | 60 |
| Bibliography..... | | 61 |