

# DIN EN ISO 22232-2:2021-09 (E)

## Non-destructive testing - Characterization and verification of ultrasonic test equipment - Part 2: Probes (ISO 22232-2:2020)

---

Contents	Page
<b>European foreword</b>	4
<b>Foreword</b>	5
<b>1 Scope</b>	6
<b>2 Normative references</b>	6
<b>3 Terms and definitions</b>	6
<b>4 Symbols</b>	8
<b>5 General requirements of conformity</b>	9
<b>6 Technical information for probes</b>	10
6.1 General	10
6.2 Probe data sheet	10
6.3 Probe test report	10
<b>7 Test equipment</b>	12
7.1 Electronic equipment	12
7.2 Test blocks and other equipment	12
<b>8 Performance requirements for probes</b>	20
8.1 Physical aspects	20
8.1.1 Procedure	20
8.1.2 Acceptance criterion	20
8.2 Pulse shape, amplitude and duration	20
8.2.1 Procedure	20
8.2.2 Acceptance criterion	21
8.3 Frequency spectrum and bandwidth	22
8.3.1 Procedure	22
8.3.2 Acceptance criteria	22
8.4 Pulse-echo sensitivity	22
8.4.1 Procedure	22
8.4.2 Acceptance criterion	23
8.5 Distance-amplitude curve	23
8.5.1 General	23
8.5.2 Procedure	23
8.5.3 Acceptance criterion	25
8.6 Beam parameters for immersion probes	25
8.6.1 General	25
8.6.2 Beam profile — Measurements performed directly on the beam	26
8.6.3 Beam profile — Measurements made using an automated scanning system	33
8.7 Beam parameters for straight-beam single-transducer contact probes	35
8.7.1 General	35
8.7.2 Beam divergence and side lobes	36
8.7.3 Squint angle and offset for straight-beam probes	37
8.7.4 Focal distance (near field length)	38
8.7.5 Focal width	38
8.7.6 Length of the focal zone	39
8.8 Beam parameters for angle-beam single-transducer contact probes	39
8.8.1 General	39
8.8.2 Index point	39

8.8.3	Beam angle and beam divergence.....	40
8.8.4	Squint angle and offset for angle-beam probes.....	43
8.8.5	Focal distance (near field length).....	46
8.8.6	Focal width.....	47
8.8.7	Length of the focal zone.....	47
8.9	Beam parameters for straight-beam dual-transducer contact probes.....	48
8.9.1	General.....	48
8.9.2	Delay line delay path.....	48
8.9.3	Focal distance.....	48
8.9.4	Axial sensitivity range (focal zone).....	48
8.9.5	Lateral sensitivity range (focal width).....	49
8.10	Beam parameters for angle-beam dual-transducer contact probes.....	50
8.10.1	General.....	50
8.10.2	Index point.....	50
8.10.3	Beam angle and profiles.....	50
8.10.4	Wedge delay path.....	51
8.10.5	Distance to sensitivity maximum (focal distance).....	51
8.10.6	Axial sensitivity range (length of the focal zone).....	51
8.10.7	Lateral sensitivity range (focal width).....	51
8.11	Crosstalk.....	52
8.11.1	Procedure.....	52
8.11.2	Acceptance criterion.....	52
<b>Annex A</b> (normative) <b>Calculation of the near field length of non-focusing probes</b>	.....	<b>53</b>
<b>Annex B</b> (informative) <b>Calibration block for angle-beam probes</b>	.....	<b>56</b>
<b>Annex C</b> (informative) <b>Determination of delay line and wedge delays</b>	.....	<b>60</b>
<b>Bibliography</b>	.....	<b>61</b>