

ISO 13067:2020 (E)

Microbeam analysis — Electron backscatter diffraction — Measurement of average grain size

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
3.1	Terminology associated with EBSD measurement of grain size
3.2	Terminology associated with grains and grain boundaries determined via EBSD
3.3	Terminology associated within grain size measurement
3.4	Terminology associated with data correction and uncertainty of EBSD maps
4	Equipment for grain sizing by EBSD
4.1	Hardware requirements
4.2	Software requirements
5	Acquiring the map for grain sizing by EBSD
5.1	Specimen preparation
5.2	Defining specimen axes
5.3	Stage positioning and calibration
5.4	Linear calibration
5.5	Preliminary examination
5.6	Choice of step size
5.7	Determination of the level of angular accuracy needed[7][8]
5.8	Choice of areas to be mapped and map size
5.9	Considerations when examining plastically deformed materials
6	Analytical procedure
6.1	Definition of boundaries
6.1.1	Grain boundary angles
6.1.2	Handling incomplete boundaries
6.1.3	Dealing with special boundaries
6.2	Post-acquisition treatment of raw data
6.3	Data-cleaning steps
6.4	Measurement of sectional grain size
6.5	Calculation of average grain size
6.6	Representation of data
7	Measurement uncertainty
8	Reporting of analysis results
Annex A	(informative) Grain size measurement
Annex B	(informative) Reproducibility