ISO 13067:2020 (E)

Microbeam analysis — Electron backscatter diffraction — Measurement of average grain size

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

- 3.1 Terminology associated with EBSD measurement of grain size
- 3.2 Terminology associated with grains and grain boundaries determined via EBSD
- 3.3 Terminology associated within grain size measurement
- 3.4 Terminology associated with data correction and uncertainty of EBSD maps

4 Equipment for grain sizing by EBSD

- 4.1 Hardware requirements
- 4.2 Software requirements

5 Acquiring the map for grain sizing by EBSD

- 5.1 Specimen preparation
- 5.2 Defining specimen axes
- 5.3 Stage positioning and calibration
- 5.4 Linear calibration
- 5.5 Preliminary examination
- 5.6 Choice of step size
- 5.7 Determination of the level of angular accuracy needed[7][8]
- 5.8 Choice of areas to be mapped and map size
- 5.9 Considerations when examining plastically deformed materials

6 Analytical procedure

- 6.1 Definition of boundaries
- 6.1.1 Grain boundary angles
- 6.1.2 Handling incomplete boundaries
- 6.1.3 Dealing with special boundaries
- 6.2 Post-acquisition treatment of raw data
- 6.3 Data-cleaning steps
- 6.4 Measurement of sectional grain size
- 6.5 Calculation of average grain size
- 6.6 Representation of data

7 Measurement uncertainty

8 Reporting of analysis results

Annex A (informative) Grain size measurement

Annex B (informative) Reproducibility

Page count: 26