

ISO 22232-2:2020 (E)

Non-destructive testing — Characterization and verification of ultrasonic test equipment — Part 2: Probes

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	General requirements of conformity
6	Technical information for probes
6.1	General
6.2	Probe data sheet
6.3	Probe test report
7	Test equipment
7.1	Electronic equipment
7.2	Test blocks and other equipment
8	Performance requirements for probes
8.1	Physical aspects
8.1.1	Procedure
8.1.2	Acceptance criterion
8.2	Pulse shape, amplitude and duration
8.2.1	Procedure
8.2.2	Acceptance criterion
8.3	Frequency spectrum and bandwidth
8.3.1	Procedure
8.3.2	Acceptance criteria
8.4	Pulse-echo sensitivity
8.4.1	Procedure
8.4.2	Acceptance criterion
8.5	Distance-amplitude curve
8.5.1	General
8.5.2	Procedure
8.5.3	Acceptance criterion
8.6	Beam parameters for immersion probes
8.6.1	General
8.6.2	Beam profile — Measurements performed directly on the beam
8.6.2.1	General
8.6.2.2	Axial profile — Focal distance and length of the focal zone
8.6.2.2.1	Procedure
8.6.2.2.2	Acceptance criteria
8.6.2.3	Transverse profile — Focal width
8.6.2.3.1	Procedure
8.6.2.3.2	Acceptance criterion
8.6.2.4	Transverse profile — Beam divergence
8.6.2.4.1	Procedure
8.6.2.4.2	Acceptance criterion
8.6.3	Beam profile — Measurements made using an automated scanning system
8.6.3.1	General

- 8.6.3.2 Beam profile by scanning means — Focal distance and focal length
- 8.6.3.2.1 Procedure
- 8.6.3.2.2 Acceptance criteria
- 8.6.3.3 Beam profile by scanning means — Focal width and beam divergence
- 8.6.3.3.1 Procedure
- 8.6.3.3.2 Acceptance criteria
- 8.7 Beam parameters for straight-beam single-transducer contact probes
- 8.7.1 General
- 8.7.2 Beam divergence and side lobes
- 8.7.2.1 Procedure
- 8.7.2.2 Acceptance criteria
- 8.7.3 Squint angle and offset for straight-beam probes
- 8.7.3.1 Procedure
- 8.7.3.2 Acceptance criteria
- 8.7.4 Focal distance (near field length)
- 8.7.4.1 Procedure
- 8.7.4.2 Acceptance criterion
- 8.7.5 Focal width
- 8.7.5.1 Procedure
- 8.7.5.2 Acceptance criterion
- 8.7.6 Length of the focal zone
- 8.7.6.1 Procedure
- 8.7.6.2 Acceptance criterion
- 8.8 Beam parameters for angle-beam single-transducer contact probes
- 8.8.1 General
- 8.8.2 Index point
- 8.8.2.1 Procedure
- 8.8.2.2 Acceptance criterion
- 8.8.3 Beam angle and beam divergence
- 8.8.3.1 Procedure
- 8.8.3.2 Acceptance criteria
- 8.8.4 Squint angle and offset for angle-beam probes
- 8.8.4.1 Procedure
- 8.8.4.2 Acceptance criteria
- 8.8.5 Focal distance (near field length)
- 8.8.5.1 Procedure
- 8.8.5.2 Acceptance criterion
- 8.8.6 Focal width
- 8.8.6.1 Procedure
- 8.8.6.2 Acceptance criterion
- 8.8.7 Length of the focal zone
- 8.8.7.1 Procedure
- 8.8.7.2 Acceptance criterion
- 8.9 Beam parameters for straight-beam dual-transducer contact probes
- 8.9.1 General
- 8.9.2 Delay line delay path
- 8.9.3 Focal distance
- 8.9.3.1 Procedure
- 8.9.3.2 Acceptance criterion
- 8.9.4 Axial sensitivity range (focal zone)
- 8.9.4.1 Procedure
- 8.9.4.2 Acceptance criterion
- 8.9.5 Lateral sensitivity range (focal width)
- 8.9.5.1 Procedure
- 8.9.5.2 Acceptance criterion
- 8.10 Beam parameters for angle-beam dual-transducer contact probes
- 8.10.1 General
- 8.10.2 Index point
- 8.10.2.1 Procedure
- 8.10.2.2 Acceptance criterion
- 8.10.3 Beam angle and profiles
- 8.10.3.1 Procedure
- 8.10.3.2 Acceptance criterion
- 8.10.4 Wedge delay path

- 8.10.4.1 Procedure
- 8.10.4.2 Acceptance criterion
- 8.10.5 Distance to sensitivity maximum (focal distance)
- 8.10.5.1 Procedure
- 8.10.5.2 Acceptance criterion
- 8.10.6 Axial sensitivity range (length of the focal zone)
- 8.10.6.1 Procedure
- 8.10.6.2 Acceptance criterion
- 8.10.7 Lateral sensitivity range (focal width)
- 8.10.7.1 Procedure
- 8.10.7.2 Acceptance criterion
- 8.11 Crosstalk
- 8.11.1 Procedure
- 8.11.2 Acceptance criterion

Annex A (normative) Calculation of the near field length of non-focusing probes

- A.1 General
- A.2 Straight-beam probes
- A.3 Angle-beam probes

Annex B (informative) Calibration block for angle-beam probes

Annex C (informative) Determination of delay line and wedge delays

- C.1 General
- C.2 Single-transducer probes
 - C.2.1 Delay line delay
 - C.2.2 Wedge delay
- C.3 Dual-transducer probes

Page count: 56