

ISO 23466:2020 (E)

Design criteria for the thermal insulation of reactor coolant system main equipments and piping of PWR nuclear power plants

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	General design procedure
4.1	General requirements
4.2	Reactor safety considerations
4.3	Material selection
4.3.1	General requirements
4.3.2	Primary insulating material
4.3.3	Outer cladding/encapsulating material
4.3.4	Support/fixation material
4.4	Design and test of thermal behaviour
4.4.1	Design of thermal behaviour
4.4.2	Test of thermal behaviour
4.5	Design and test of mechanical properties
4.5.1	Design of mechanical properties
4.5.2	Test of mechanical properties
4.6	Additional requirements
5	Design requirements of RPV thermal insulation
5.1	General requirements
5.2	Safety requirements
5.3	Material selection
5.4	Thermal behaviour requirements
5.5	Mechanical properties and structural requirements
6	Design requirements of thermal insulation of RCS piping and other equipment
6.1	General requirements
6.2	Safety requirements
6.3	Material selection
6.4	Thermal behaviour requirements
6.5	Mechanical properties and structural requirements
Annex A	(informative) Geometry description of metallic thermal insulation
A.1	General
Annex B	(informative) Geometry description of non-metallic thermal insulation
B.1	General
B.2	Non-metallic thermal insulation composed by thermal insulation panels
B.3	Non-metallic thermal insulation composed by strapped layers
Annex C	(informative) Type of RPV thermal insulation with RPV external cooling safety functionality
C.1	General
C.2	Design recommendations
Annex D	(informative) Type of RPV thermal insulation with radiation shield safety functionality
D.1	General