ISO 10140-1:2021 (E)

Acoustics — Laboratory measurement of sound insulation of building elements — Part 1: Application rules for specific products

Contents

| | | Foreword |
|-------|--------------|--|
| | | Introduction |
| 1 | | Scope |
| 2 | | Normative references |
| 3 | | Terms and definitions |
| 4 | | General |
| 5 | | Structure of application rules for specific products |
| Annex | κA | (normative) Walls — Airborne sound insulation |
| | A.1 | General |
| | A.2 | Test element |
| | | |
| | A.3 | Boundary and mounting conditions |
| | A.4 | Test and operating conditions |
| | A.5 | Test report |
| Annex | В | (normative) Doors — Airborne sound insulation |
| | B.1 | General |
| | B.2 | Test element |
| | B.3 | Boundary and mounting conditions |
| | B.4 | Test and operating conditions |
| | B.5 | Test report |
| Annex | | (normative) Windows — Airborne sound insulation |
| | C.1 | General |
| | C.2 | Test element |
| | | |
| | C.3 | Boundary and mounting conditions |
| | C.4 | Test and operating conditions |
| | C.4. | · · · · · J |
| | C.4. | 2 Operation |
| | C.5 | Test report |
| Annex | D | (normative) Glazing — Airborne sound insulation |
| | D.1 | General |
| | D.2 | Test element |
| | D.3 | Boundary and mounting conditions |
| | D.4 | Test and operating conditions |
| | D.4. | 1 General |
| | D.4. | 2 Reference curves |
| | D.4. | |
| | D.4. | |
| | | |
| | D.4. | |
| | D.4.: D.5 | 2.4 Maximum standard deviation of repeatability Test report |
| Annex | | (normative) Small technical elements — Airborne sound insulation |
| | E.1 | General |
| | E.2 | Test element |
| | L.Z | I GOL GIGINGIN |

| E E E E | E.2.2 E.2.3 E.2.4 E.2.5 E.2.5.1 E.2.5.2 E.2.5.3 | General Number of positions Local increase of wall thickness Local decrease of wall thickness Central, corner and edge positions Equipment used away from walls Equipment used near an edge Equipment used near a corner Simulation of corner or edge positions |
|------------------|---|---|
| E | E.3 E.3.1 | Boundary and mounting conditions Air transfer devices Electrical raceways |
| E | ≣. 4 | Test and operating conditions Test report |
| Annex I | F (norma | ative) Floors — Airborne and impact sound insulation |
| F | ₹.1 | General |
| _ | | Test element |
| | | Boundary and mounting conditions |
| | | Test and operating conditions |
| r | F.5 | Test report |
| Annex (| G (norma | ative) Acoustical linings — Improvement of airborne sound insulation |
| (| G.1 | General |
| | | Test element |
| | | Boundary and mounting conditions |
| | | Test and operating conditions |
| (| | Test report |
| Annex I | H (norma | ative) Floor coverings — Improvement of impact sound insulation |
| | | General |
| | | Test element |
| | | General |
| | | Classification of floor coverings |
| | | Category I — Small specimens |
| | | Category II — Large specimens |
| | | Category III — Stretched materials Materials of uncertain classification |
| _ | | |
| | | Boundary and mounting conditions Test and operating conditions |
| | | Load |
| | | Installation |
| | | Adhesive mounting |
| | | Curing |
| H | | Environmental conditions |
| H | 1.4.6 | Position of the tapping machine |
| H | 1.4.6.1 | Floor coverings on a heavyweight reference floor |
| | | Testing floor coverings of category I |
| | | Testing floor coverings of category II or III |
| | | Testing floor coverings on a lightweight reference floor |
| | | Testing floor coverings of category I |
| | | Testing floor coverings of category II or III Test report |
| | | Additional information |
| | | Improvement with heavy/soft impact |
| | 1.6.2 | Procedures using a wooden mock-up floor to determine the impact sound improvement of floor coverings when mounted on lightweight floor constructions |
| | | General |
| | | Test arrangement |
| | | Preparation and installation of test specimen |
| | | Test procedure |
| | | Expression of results |

Annex I (normative) Shutters — Airborne sound insulation

| | I.1 | General | | |
|--|-------|--|--|--|
| | 1.2 | Test element | | |
| | 1.3 | Boundary and mounting conditions | | |
| | 1.4 | Test and operating conditions | | |
| | 1.4.1 | Conditioning | | |
| | 1.4.2 | Operation | | |
| | 1.5 | Test report | | |
| Annex J (normative) Joints filled with fillers or seals — Sound reduction index | | | | |
| | J.1 | General | | |
| | J.2 | Test element | | |
| | J.2.1 | General | | |
| | J.2.2 | Illustration 1 — Gaps between windows and doors | | |
| J.2.3 | | Illustration 2 — Test element for slits and gaps | | |
| | J.3 | Boundary and mounting conditions | | |
| | J.3.1 | General | | |
| J.3.2 J.3.3 | | Illustration 1 — Geometry of a joint to test fillers in a cassette | | |
| | | Illustration 2 — Geometry of a joint to test gaskets | | |
| | J.4 | Test and operating conditions | | |
| | J.5 | Test report | | |
| | J.5.1 | Expression of results | | |
| | J.5.2 | Test report | | |
| Annex K (normative) Roofs, roof/ceiling systems, roof windows/skylights and rooflights — Rasound | | | | |
| | | | | |
| | K.1 | General | | |
| | K.2 | Test element | | |
| K.2.1 | | Standard element and laboratory configuration | | |
| K.2.2 | | Other configurations | | |
| | K.3 | Boundary and mounting conditions | | |
| | K.4 | Test and operating conditions | | |
| | K.4.1 | General | | |
| | K.4.2 | Determination of the sound intensity level (indirect method) | | |
| | K.4.3 | Direct measurement of sound intensity | | |
| | K.5 | Test report | | |
| | K.6 | Additional information — Normalization using a reference test specimen | | |

Page count: 54