

# DIN EN 1744-4:2022-03 (E)

## Tests for chemical properties of aggregates - Part 4: Determination of water susceptibility of fillers for bituminous mixtures

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
1	Scope .....	5
2	Normative references .....	5
3	Terms and definitions .....	6
4	Principle .....	6
5	Separation of filler from a bitumen filler mixture .....	7
5.1	Reagents .....	7
5.2	Apparatus .....	7
Figure 1 -- T-shaped stirrer .....		8
5.3	Sampling .....	9
5.4	Preparation of test portions .....	9
5.5	Procedure .....	9
5.6	Calculation and expression of results .....	10
5.7	Test report .....	10
Annex A (normative) Determination of the volume increase and loss of stability of a Marshall specimen .....		11
A.1	General .....	11
A.2	Principle .....	11
A.3	Materials .....	11
A.4	Apparatus .....	11
A.5	Sampling .....	12
Table A.1 -- Mass of test portions .....		12
A.6	Preparation of Marshall specimens .....	12
Table A.2 -- Proportion of the aggregates .....		13
A.7	Procedure .....	13
A.8	Calculation and expression of results .....	13
A.9	Test report .....	14
A.10	Precision .....	14
Table A.3 -- Repeatability (same observer, same apparatus) .....		14
Table A.4 -- Reproducibility (different observers, different apparatus) .....		15
Annex B (informative) Water susceptibility of fillers - Shaking abrasion method .....		16
B.1	General .....	16
B.2	Principle .....	16
B.3	Apparatus .....	16
Figure B.1 -- Shaking device .....		17
B.4	Materials .....	17

<b>B.5</b>	<b>Preparation of the specimens .....</b>	<b>17</b>
<b>B.5.1</b>	<b>Composition of the specimen mixture .....</b>	<b>17</b>
<b>Table B.1 -- Proportion of particle size classifications applied in the specimen mixture when determining water susceptibility using the shaking abrasion method .....</b>		
		<b>18</b>
<b>Table B.2 -- Specimen mixture composition for determining water susceptibility using the shaking abrasion method .....</b>		
		<b>18</b>
<b>B.5.2</b>	<b>Preparation of the specimen mixture .....</b>	<b>18</b>
<b>B.5.3</b>	<b>Manufacturing the specimens .....</b>	<b>19</b>
<b>B.6</b>	<b>Procedure .....</b>	<b>19</b>
<b>B.6.1</b>	<b>Determining water absorption and swelling .....</b>	<b>19</b>
<b>B.6.2</b>	<b>Determining the shaking abrasion .....</b>	<b>20</b>
<b>B.6.3</b>	<b>Calculation and expression of results .....</b>	<b>20</b>
<b>B.6.3.1</b>	<b>Bulk density of the composite aggregate 0/0,4 mm .....</b>	<b>20</b>
<b>B.6.3.2</b>	<b>Water absorption .....</b>	<b>21</b>
<b>B.6.3.3</b>	<b>Swelling .....</b>	<b>21</b>
<b>B.6.3.4</b>	<b>Shaking abrasion .....</b>	<b>22</b>
<b>B.7</b>	<b>Test report .....</b>	<b>22</b>
<b>Table B.3 -- Example of tabular representation .....</b>		
		<b>22</b>
<b>Bibliography .....</b>		
		<b>23</b>