

# ISO 1143:2021 (E)

## Metallic materials — Rotating bar bending fatigue testing

---

### Contents

|         |   |
|---------|---|
|         | Foreword  |
| 1       | Scope   |
| 2       | Normative references  |
| 3       | Terms and definitions   |
| 4       | Symbols   |
| 5       | Principle of test   |
| 6       | Shape and size of specimen  |
| 6.1     | Forms of the test section   |
| 6.2     | Dimensions of specimens   |
| 7       | Preparation of specimens  |
| 7.1     | General   |
| 7.2     | Selection of the specimen and marking   |
| 7.3     | Machining procedure   |
| 7.3.1   | Heat treatment of test material   |
| 7.3.2   | Machining criteria  |
| 7.3.3   | Surface condition of specimens  |
| 7.3.4   | Dimensional checks  |
| 7.4     | Storage and handling  |
| 8       | Accuracy of the testing apparatus   |
| 9       | Heating device and temperature measurement  |
| 10      | Test procedure  |
| 10.1    | Mounting the specimen   |
| 10.2    | Application of force  |
| 10.3    | Frequency selection   |
| 10.4    | End of test   |
| 10.5    | Procedure for testing at elevated temperature   |
| 11      | Test report   |
| 12      | Presentation of fatigue test results  |
| 12.1    | Tabular presentation  |
| 12.2    | Graphical presentation  |
| 13      | Measurement uncertainty   |
| 13.1    | General   |
| 13.2    | Test conditions   |
| 13.3    | Test results  |
| Annex A | (normative) Verification of the bending moment of rotating bar bending fatigue machines |
| A.1     | Verification philosophies for rotating bar bending fatigue machines                     |
| A.2     | Verification equipment  |
| A.2.1   | General   |
| A.2.2   | Masses  |
| A.2.3   | Force transducers   |

- A.2.4 Dimensional measurement
- A.3 Inspection of the test machine prior to verification
- A.4 Verification procedure — Verification by dimensional measurement
  - A.4.1 General
  - A.4.2 Temperature stabilization
  - A.4.3 Measurement of mean force arm length
  - A.4.4 Measurement of loading arm lever ratio
  - A.4.5 Calculation of required characteristics — Relative force accuracy error,  $q$ 
    - A.4.5.1 Machines incorporating force transducer(s)
    - A.4.5.2 Machines using test masses
      - A.4.5.3 Machines using steelyard and balance loading
  - A.4.6 Calculation of required characteristics — Relative force repeatability error,  $b$ 
    - A.4.6.1 Machines incorporating force transducer(s); i.e. force transducer(s)
      - A.4.6.2 Machines using test masses
        - A.4.6.3 Machines using steelyard and balance loading
  - A.4.7 Calculation of required characteristics — Relative force arm accuracy error,  $q'$
  - A.4.8 Calculation of required characteristics — Relative moment accuracy error,  $q''$
  - A.4.9 Required performance characteristics
- A.5 Verification procedure — Verification using strain-gauged specimen
  - A.5.1 General
  - A.5.2 Temperature stabilization
  - A.5.3 Pre-verification conditioning
  - A.5.4 Selection of test forces
  - A.5.5 Cantilever machines
    - A.5.6 Four-point bending machines
      - A.5.7 Machines verified using a strain-gauged specimen
  - A.5.8 Calculation of required characteristics — Relative force accuracy error,  $q$ 
    - A.5.8.1 Machines incorporating force transducer(s)
      - A.5.8.2 Machines using test masses
        - A.5.8.3 Machines using steelyard and balance loading
  - A.5.9 Calculation of required characteristics — Relative force repeatability error,  $b$ 
    - A.5.9.1 Machines incorporating force transducer(s); i.e. force transducer(s)
      - A.5.9.2 Machines using test masses
        - A.5.9.3 Machines using steelyard and balance loading
  - A.5.10 Required performance characteristics
- A.6 Verification period

**Annex B (informative) Example of a test report**

Page count: 26