

# ISO 12135:2021 (E)

## Metallic materials — Unified method of test for the determination of quasistatic fracture toughness

---

### Contents

|           |                                    |
|-----------|------------------------------------|
|           | Foreword                           |
| 1         | Scope                              |
| 2         | Normative references               |
| 3         | Terms and definitions              |
| 4         | Symbols and abbreviated terms      |
| 5         | General requirements               |
| 5.1       | General                            |
| 5.2       | Fracture parameters                |
| 5.3       | Fracture toughness symbols         |
| 5.4       | Test specimens                     |
| 5.4.1     | Specimen configuration and size    |
| 5.4.2     | Specimen preparation               |
| 5.4.2.1   | Material condition                 |
| 5.4.2.2   | Crack plane orientation            |
| 5.4.2.3   | Machining                          |
| 5.4.2.4   | Fatigue precracking                |
| 5.4.2.4.1 | General                            |
| 5.4.2.4.2 | Equipment and fixtures             |
| 5.4.2.4.3 | Bend specimens                     |
| 5.4.2.4.4 | Compact specimens                  |
| 5.4.2.5   | Side grooving                      |
| 5.5       | Pre-test requirements              |
| 5.5.1     | Pre-test measurements              |
| 5.5.2     | Crack shape/length requirements    |
| 5.6       | Test apparatus                     |
| 5.6.1     | Calibration                        |
| 5.6.2     | Force application                  |
| 5.6.3     | Displacement measurement           |
| 5.6.4     | Test fixtures                      |
| 5.7       | Test requirements                  |
| 5.7.1     | Three-point bend testing           |
| 5.7.1.1   | Specimen fixture alignment         |
| 5.7.1.2   | Crack-tip opening displacement     |
| 5.7.1.3   | J-integral                         |
| 5.7.2     | Compact tension testing            |
| 5.7.2.1   | Specimen and fixture alignment     |
| 5.7.2.2   | Crack-tip opening displacement     |
| 5.7.2.3   | J-integral                         |
| 5.7.3     | Specimen test temperature          |
| 5.7.4     | Recording                          |
| 5.7.5     | Testing rates                      |
| 5.7.6     | Test analyses                      |
| 5.8       | Post-test crack measurements       |
| 5.8.1     | General                            |
| 5.8.2     | Initial crack length, $a_0$        |
| 5.8.3     | Stable crack extension, $\Delta a$ |
| 5.8.4     | Unstable crack extension           |

- 6           **Determination of fracture toughness for stable and unstable crack extension**
  - 6.1           General
  - 6.2           Determination of plane strain fracture toughness,  $K_{Ic}$ 
    - 6.2.1          General
    - 6.2.2          Interpretation of the test record for FQ
    - 6.2.3          Calculation of  $K_Q$
    - 6.2.4          Qualification of  $K_Q$  as  $K_{Ic}$
  - 6.3           Determination of fracture toughness in terms of  $\delta$ 
    - 6.3.1          Determination of  $F_c$  and  $V_c$ ,  $F_u$  and  $V_u$ , or  $F_{uc}$  and  $V_{uc}$
    - 6.3.2          Determination of  $F_m$  and  $V_m$
    - 6.3.3          Determination of  $V_p$
    - 6.3.4          Calculation of  $\delta_0$
    - 6.3.5          Qualification of  $\delta_0$  fracture toughness value
  - 6.4           Determination of fracture toughness in terms of  $J$ 
    - 6.4.1          Determination of  $F_c$  and  $V_c$  or  $q_c$ ,  $F_u$  and  $V_u$  or  $q_u$ , or  $F_{uc}$  and  $V_{uc}$  or  $q_{uc}$
    - 6.4.2          Determination of  $F_m$  and  $q_m$
    - 6.4.3          Determination of  $U_p$
    - 6.4.4          Calculation of  $J_0$
    - 6.4.5          Qualification of  $J_0$  fracture toughness value
- 7           **Determination of resistance curves  $\delta$ - $\Delta a$  and  $J$ - $\Delta a$  and initiation toughness  $\delta_{0,2BL}$  and  $J_{0,2BL}$  and  $\delta_i$  and  $J_i$  for stable crack extension**
  - 7.1           General
  - 7.2           Test procedure
    - 7.2.1          General
    - 7.2.2          Multiple-specimen procedure
    - 7.2.3          Single-specimen procedure
    - 7.2.4          Final crack front straightness
  - 7.3           Calculation of  $J$  and  $\delta$ 
    - 7.3.1          Calculation of  $J$
    - 7.3.2          Calculation of  $\delta$
  - 7.4           R-curve plot
    - 7.4.1          Plot construction
    - 7.4.2          Data spacing and curve fitting
  - 7.5           Qualification of resistance curves
    - 7.5.1          Qualification of  $J$ - $\Delta a$  resistance curves
      - 7.5.1.1         $J_{max}$  is calculated for each specimen as the smallest of:
    - 7.5.2          Qualification of  $\delta$ - $\Delta a$  resistance curves
  - 7.6           Determination and qualification of  $J_{0,2BL}$  and  $\delta_{0,2BL}$ 
    - 7.6.1          Determination of  $J_{0,2BL}$
    - 7.6.2          Determination of  $\delta_{0,2BL}$
  - 7.7           Determination of initiation toughness  $J_i$  and  $\delta_i$  by scanning electron microscopy (SEM)
- 8           **Test report**
  - 8.1           Organization
  - 8.2           Specimen, material and test environment
    - 8.2.1          Specimen description
    - 8.2.2          Specimen dimensions
    - 8.2.3          Material description
    - 8.2.4          Additional dimensions
    - 8.2.5          Test environment
    - 8.2.6          Fatigue precracking conditions
  - 8.3           Test data qualification
    - 8.3.1          Limitations
    - 8.3.2          Crack length measurements
    - 8.3.3          Fracture surface appearance
    - 8.3.4          Pop-in
    - 8.3.5          Resistance curves
  - 8.3.6          Checklist for data qualification
  - 8.4           Qualification of  $K_{Ic}$
  - 8.5           Qualification of  $\delta_c(B)$ ,  $\delta_u(B)$ ,  $\delta_{uc}(B)$  or  $\delta_m(B)$
  - 8.6           Qualification of  $J_c(B)$ ,  $J_u(B)$ ,  $J_{uc}(B)$  or  $J_m(B)$
  - 8.7           Qualification of the  $\delta$ -R Curve

|  |  |
|--|--|
| 8.8  | Qualification of the J-R Curve   |
| 8.9  | Qualification of $\delta_{0,2BL}(B)$ as $\delta_{0,2BL}$   |
| 8.10   | Qualification of $J_{0,2BL}(B)$ as $J_{0,2BL}$   |
| <b>Annex A (informative) Determination of <math>\delta_i</math> and <math>J_i</math></b>                       |  |
| A.1  | General  |
| A.2  | Critical stretch zone width (SZW) measurement  |
| A.3  | Determination of $\delta_i$  |
| A.4  | Determination of $J_i$   |
| <b>Annex B (normative) Crack plane orientation</b>   |  |
| <b>Annex C (informative) Example test reports</b>  |  |
| C.1  | Specimen, material and test environment  |
| C.2  | Data qualification   |
| C.3  | Resistance curve data  |
| C.4  | Qualification of KQ as K <sub>Ic</sub>   |
| C.5  | Qualification of $\delta_c(B)$ , $\delta_u(B)$ , $\delta_{uc}(B)$ or $\delta_m(B)$                             |
| C.6  | Qualification of $J_c(B)$ , $J_u(B)$ , $J_{uc}(B)$ or $J_m(B)$   |
| C.7  | Qualification of $\delta$ -R curve   |
| C.8  | Qualification of J-R curve   |
| C.9  | Qualification of $\delta_{Q0,2BL}(B)$ as $\delta_{0,2BL}$  |
| C.10   | Qualification of $J_{Q0,2BL}$ as $J_{0,2BL}$   |
| <b>Annex D (informative) Stress intensity factor coefficients and compliance relationships</b>                 |  |
| D.1  | Stress intensity factor coefficients   |
| D.1.1  | Three-point bend specimens   |
| D.1.2  | Compact specimens  |
| D.2  | Elastic compliance relationship  |
| D.2.1  | Three-point bend specimens instrumented for measurement of force F versus crack-mouth opening displacement VM1 |
| D.2.2  | Compact specimens instrumented for measurement of F versus crack-mouth opening displacement VM2                |
| D.2.3  | Three-point bend specimens instrumented for measurement of F versus load-line displacement $q_{e1}$            |
| D.2.4  | Compact specimens instrumented for measurement of F versus load-line displacement $q_{e2}$                     |
| <b>Annex E (informative) Measurement of load-line displacement q in the three-point bend test</b>              |  |
| <b>Annex F (informative) Derivation of pop-in formulae</b>   |  |
| <b>Annex G (informative) Analytical methods for the determination of <math>V_p</math> and <math>U_p</math></b> |  |
| G.1  | General  |
| G.2  | Plastic displacement, $V_p$  |
| G.3  | Plastic area, $U_p$  |
| <b>Annex H (informative) Guidelines for single-specimen methods</b>  |  |
| H.1  | General  |
| H.2  | Unloading compliance technique   |
| H.3  | Test recommendations   |
| H.3.1  | Compliance measurement   |
| H.3.2  | Digital signal resolution  |
| H.3.3  | Autographic signal resolution  |
| H.4  | Procedure  |
| H.4.1  | Precycling   |
| H.4.2  | Loading rate   |
| H.4.3  | Crack length measurements  |
| H.4.4  | Termination of test  |
| H.5  | Crack length calculation   |
| H.5.1  | Bend specimen: Crack-mouth opening displacement (CMOD) measured at the specimen surface                        |
| H.5.2  | Bend specimen: Compliance based on load-point displacement   |
| H.5.3  | Compact specimens  |

|         |   |
|---------|---|
| H.5.4   | Rotation correction for compact specimens |
| H.6     | Resistance to crack extension             |
| H.6.1   | General                                   |
| H.6.2   | Estimated initial crack length            |
| H.6.3   | Estimated crack extension                 |
| H.6.4   | Resistance curves                         |
| H.7     | Electrical potential techniques           |
| H.7.1   | AC potential method                       |
| H.7.2   | Interpretation of test records            |
| H.8     | DC potential methods                      |
| H.8.1   | Method 1                                  |
| H.8.1.1 | Procedure                                 |
| H.8.1.2 | Interpretation of test records            |
| H.8.2   | Method 2                                  |
| H.8.2.1 | Procedure                                 |
| H.8.2.2 | Interpretation of test records            |

Annex I (normative) Power-law fits to crack extension data (see Reference [42])

Page count: 100