ISO 7539-9:2021 (E)

Corrosion of metals and alloys — Stress corrosion testing — Part 9: Preparation and use of pre-cracked specimens for tests under rising load or rising displacement

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Principle

5 Specimens

- 5.1 General
- 5.2 Specimen design
- 5.3 Stress intensity factor considerations
- 5.4 Specimen preparation
- 5.5 Specimen identification

6 Initiation and propagation of fatigue cracks

7 Procedure

- 7.1 General
- 7.2 Environmental considerations
- 7.3 Environmental chamber
- 7.4 Environmental control and monitoring
- 7.5 Selection of initial K value prior to dynamic loading
- 7.6 Determination of KISCC
- 7.6.1 General
- 7.6.2 Determination schedule
- 7.6.3 Validation of test results
- 7.7 Determination of crack velocity

8 Test report

Annex A (informative) Determination of a suitable displacement rate for determining KISCC from constant displacement rate tests

- A.1 General
- A.2 Procedure

Annex B (informative) Determination of crack growth velocity

Annex C (informative) Information on indirect methods for measuring crack length (see also ISO 21153)

- C.1 Electrical resistance measurement methods
- C.1.1 Direct current (DC) potential drop method
- C.1.2 AC potential drop methods
- C.2 Compliance methods

Page count: 32