

# ISO 23703:2022-01 (E)

## Microbeam analysis - Guidelines for misorientation analysis to assess mechanical damage of austenitic stainless steel by electron backscatter diffraction (EBSD)

---

Contents	Page
Foreword.....	iv
Introduction.....	v
<b>1 Scope.....</b>	<b>1</b>
<b>2 Normative references.....</b>	<b>1</b>
<b>3 Terms and definitions.....</b>	<b>1</b>
<b>4 Abbreviated terms.....</b>	<b>4</b>
<b>5 Equipment for EBSD measurement.....</b>	<b>4</b>
<b>6 Preparation.....</b>	<b>4</b>
6.1 Calibration.....	4
6.2 Specimen preparation.....	5
<b>7 Measurement procedures.....</b>	<b>6</b>
7.1 Setting SEM operating conditions.....	6
7.1.1 Accelerating voltage.....	6
7.1.2 Probe current.....	6
7.1.3 Magnification observation.....	6
7.1.4 Working distance.....	6
7.1.5 Focus.....	6
7.2 Setting the EBSD measurement conditions.....	6
7.2.1 Background correction.....	6
7.2.2 Binning.....	7
7.2.3 Pattern averaging.....	7
7.2.4 Hough transform.....	7
7.2.5 Measurement area.....	7
7.2.6 Step size.....	7
7.2.7 Scanning grid.....	8
<b>8 Calculation of misorientation.....</b>	<b>8</b>
8.1 Defining grains.....	8
8.1.1 General.....	8
8.1.2 Setting the misorientation to define grains.....	8
8.1.3 Setting of minimum grain size.....	8
8.1.4 Caution.....	8
8.2 Data screening.....	8
8.2.1 Evaluation of reliability of measured data.....	8
8.2.2 Treatment of blank pixels.....	9
8.3 Calculation of misorientation parameters.....	9
<b>9 Material damage assessment.....</b>	<b>11</b>
9.1 General.....	11
9.2 Misorientation parameter for qualitative assessments.....	12
9.3 Misorientation parameter for quantitative assessments.....	12
<b>10 Report.....</b>	<b>12</b>
<b>Annex A (informative) Round robin crystal orientation measurement for damage assessment.....</b>	<b>15</b>
<b>Bibliography.....</b>	<b>25</b>