ISO 23703:2022-01 (E)

Microbeam analysis - Guidelines for misorientation analysis to assess mechanical damage of austenitic stainless steel by electron backscatter diffraction (EBSD)

Contents

Page

Foreword ... **iv**

Introduction ... **v**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **1**

4 Abbreviated terms ... **4**

5 Equipment for EBSD measurement ... **4**

6 Preparation ... **4**
6.1 Calibration ... 4
6.2 Specimen preparation ... 5

7 Measurement procedures ... **6**
7.1 Setting SEM operating conditions ... 6
7.1.1 Accelerating voltage ... 6
7.1.2 Probe current ... 6
7.1.3 Magnification observation ... 6
7.1.4 Working distance ... 6
7.1.5 Focus ... 6
7.2 Setting the EBSD measurement conditions ... 6
7.2.1 Background correction ... 6
7.2.2 Binning ... 7
7.2.3 Pattern averaging ... 7
7.2.4 Hough transform ... 7
7.2.5 Measurement area ... 7
7.2.6 Step size ... 7
7.2.7 Scanning grid ... 8

8 Calculation of misorientation ... **8**
8.1 Defining grains ... 8
8.1.1 General ... 8
8.1.2 Setting the misorientation to define grains ... 8
8.1.3 Setting of minimum grain size ... 8
8.1.4 Caution ... 8
8.2 Data screening ... 8
8.2.1 Evaluation of reliability of measured data ... 8
8.2.2 Treatment of blank pixels ... 9
8.3 Calculation of misorientation parameters ... 9

9 Material damage assessment ... **11**
9.1 General ... 11
9.2 Misorientation parameter for qualitative assessments ... 12
9.3 Misorientation parameter for quantitative assessments ... 12

10 Report ... **12**

Annex A (informative) **Round robin crystal orientation measurement for damage assessment** ... **15**

Bibliography ... **25**