

ISO 23703:2022-01 (E)

Microbeam analysis - Guidelines for misorientation analysis to assess mechanical damage of austenitic stainless steel by electron backscatter diffraction (EBSD)

Contents	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Abbreviated terms.....	4
5 Equipment for EBSD measurement.....	4
6 Preparation.....	4
6.1 Calibration.....	4
6.2 Specimen preparation.....	5
7 Measurement procedures.....	6
7.1 Setting SEM operating conditions.....	6
7.1.1 Accelerating voltage.....	6
7.1.2 Probe current.....	6
7.1.3 Magnification observation.....	6
7.1.4 Working distance.....	6
7.1.5 Focus.....	6
7.2 Setting the EBSD measurement conditions.....	6
7.2.1 Background correction.....	6
7.2.2 Binning.....	7
7.2.3 Pattern averaging.....	7
7.2.4 Hough transform.....	7
7.2.5 Measurement area.....	7
7.2.6 Step size.....	7
7.2.7 Scanning grid.....	8
8 Calculation of misorientation.....	8
8.1 Defining grains.....	8
8.1.1 General.....	8
8.1.2 Setting the misorientation to define grains.....	8
8.1.3 Setting of minimum grain size.....	8
8.1.4 Caution.....	8
8.2 Data screening.....	8
8.2.1 Evaluation of reliability of measured data.....	8
8.2.2 Treatment of blank pixels.....	9
8.3 Calculation of misorientation parameters.....	9
9 Material damage assessment.....	11
9.1 General.....	11
9.2 Misorientation parameter for qualitative assessments.....	12
9.3 Misorientation parameter for quantitative assessments.....	12
10 Report.....	12
Annex A (informative) Round robin crystal orientation measurement for damage assessment.....	15
Bibliography.....	25