ISO 2782-1:2022-04 (E)

Rubber, vulcanized or thermoplastic - Determination of permeability to gases - Part 1: Differential-pressure methods

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Principle 2

5 Pressure sensor method 2
5.1 Apparatus 2
5.2 Calibration 4
5.3 Test gas 4
5.4 Test pieces 5
5.4.1 Shape and dimensions 5
5.4.2 Preparation 5
5.4.3 Number of test pieces 5
5.4.4 Measurement of thickness 5
5.4.5 Time interval between forming and testing 5
5.5 Conditioning 5
5.6 Test conditions 5
5.7 Gas transmission area 6
5.8 Procedure 6
5.9 Calculation and expression of results 7
5.9.1 Gas transmission rate 7
5.9.2 Gas permeability coefficient 8
5.9.3 Gas diffusion coefficient 8
5.9.4 Gas solubility coefficient 8

6 Simplifiedpressuresensormethod 9
6.1 Apparatus 9
6.1.1 Test cell 9
6.1.2 Test piece support 9
6.1.3 Two pressure sensors 9
6.1.4 Test gas supply reservoir 9
6.1.5 Temperature sensor 9
6.2 Calibration 10
6.3 Test gas 10
6.4 Test pieces 11
6.4.1 Shape and dimensions 11
6.4.2 Preparation 11
6.4.3 Number of test pieces 11
6.4.4 Measurement of thickness 11
6.4.5 Time interval between forming and testing 11
6.5 Conditioning 11
6.6 Test conditions 11
6.7 Gas transmission area 11
6.8 Procedure 11

6.9 Calculation and expression of results 12
6.9.1 Gas permeability coefficient 12

7 Gas-chromatographic method 12
7.1 Apparatus 12
7.2 Calibration 14
7.3 Test gas 14
7.4 Carrier gas 14
7.5 Test pieces 14

7.5.1 Shape and dimensions 14
7.5.2 Preparation 14
7.5.3 Number of test pieces 14
7.5.4 Measurement of thickness 14
7.5.5 Time interval between forming and testing 14
7.6 Conditioning 14
7.7 Test conditions 14
7.8 Gas transmission area 14
7.9 Calibration curve 14
7.10 Procedure 15
7.11 Calculation and expression of results 16
7.11.1 Gas transmission rate 16
7.11.2 Gas permeability coefficient 16

8 Test report 16

Annex A (normative) Calibration schedule 18