

# DIN EN ISO 18563-1:2022-12 (E)

## Non-destructive testing - Characterization and verification of ultrasonic phased array equipment - Part 1: Instruments ( ISO 18563-1:2022)

---

<b>Contents</b>		<b>Page</b>
European foreword.....		4
Foreword.....		5
<b>1</b>	<b>Scope</b> .....	<b>6</b>
<b>2</b>	<b>Normative references</b> .....	<b>6</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>6</b>
<b>4</b>	<b>Symbols and abbreviated terms</b> .....	<b>7</b>
<b>5</b>	<b>General requirements of conformity</b> .....	<b>9</b>
<b>6</b>	<b>Manufacturer's technical specification for ultrasonic phased array instruments</b> .....	<b>9</b>
<b>7</b>	<b>Performance requirements for ultrasonic phased array instruments</b> .....	<b>13</b>
<b>8</b>	<b>Group 1 tests</b> .....	<b>15</b>
8.1	Equipment required for group 1 tests.....	15
8.2	Battery operational time.....	16
8.2.1	General.....	16
8.2.2	Procedure.....	16
8.2.3	Acceptance criterion.....	17
8.3	Stability after warm-up time.....	17
8.3.1	Procedure.....	17
8.3.2	Acceptance criteria.....	19
8.4	Stability against temperature.....	19
8.4.1	Procedure.....	19
8.4.2	Acceptance criteria.....	19
8.5	Stability against voltage variations.....	20
8.5.1	Procedure.....	20
8.5.2	Acceptance criteria.....	20
8.6	Deviation of time base.....	20
8.6.1	General.....	20
8.6.2	Procedure.....	20
8.6.3	Acceptance criterion.....	22
8.7	Transmitter.....	22
8.7.1	General.....	22
8.7.2	Pulse repetition frequency.....	22
8.7.3	Effective output impedance.....	22
8.7.4	Resolution of time delay.....	23
8.8	Receiver.....	24
8.8.1	General.....	24
8.8.2	Cross-talk attenuation between receivers.....	24
8.8.3	Dead time after the transmitter pulse.....	25
8.8.4	Dynamic range and maximum input voltage.....	27
8.8.5	Receiver input impedance.....	29
8.8.6	Time-corrected gain (TCG).....	29
8.8.7	Resolution of time delay.....	30
8.8.8	Linearity of vertical display against frequency.....	31
8.8.9	Summation.....	31
8.9	Gates.....	32
8.9.1	General.....	32

8.9.2	Linearity of gate amplitude	33
8.9.3	Linearity of time-of-flight in the gate	34
8.9.4	Monitor gates with analogue outputs	35
8.10	Highest digitized frequency	37
8.10.1	Procedures	37
8.10.2	Acceptance criterion	39
8.11	Response time of ultrasonic phased array instrument	39
8.11.1	General	39
8.11.2	Procedure	39
8.11.3	Acceptance criterion	41
<b>9</b>	<b>Group 2 tests</b>	<b>41</b>
9.1	Equipment required for group 2 tests	41
9.2	Physical state and external aspects	41
9.2.1	Procedure	41
9.2.2	Acceptance criteria	41
9.3	Transmitter	41
9.3.1	General	41
9.3.2	Transmitter pulse voltage, rise time and duration	41
9.3.3	Linearity of time delays	44
9.4	Receiver	44
9.4.1	General	44
9.4.2	Frequency response	44
9.4.3	Equivalent input noise	46
9.4.4	Linearity of gain	47
9.4.5	Variation of channel gain	48
9.4.6	Linearity of vertical display	49
9.4.7	Linearity of time delay	50
	<b>Bibliography</b>	<b>52</b>