

# DIN EN ISO 17636-2:2023-05 (E)

## Non-destructive testing of welds - Radiographic testing - Part 2: X- and gamma-ray techniques with digital detectors (ISO 17636-2:2022, Corrected version 2023-02)

---

| <b>Contents</b>         |  | <b>Page</b> |
|-------------------------|--|-------------|
| European foreword ..... |  | 4           |
| Foreword.....           |  | 5           |
| <b>1</b>                | <b>Scope</b> .....   | <b>7</b>    |
| <b>2</b>                | <b>Normative references</b> .....  | <b>7</b>    |
| <b>3</b>                | <b>Terms and definitions</b> .....   | <b>8</b>    |
| <b>4</b>                | <b>Symbols and abbreviated terms</b> .....   | <b>12</b>   |
| <b>5</b>                | <b>Classification of radiographic techniques and compensation principles</b> .....   | <b>14</b>   |
| 5.1                     | Classification.....  | 14          |
| 5.2                     | Compensation principles, CP I, CP II or CP III.....  | 14          |
| 5.2.1                   | General.....   | 14          |
| 5.2.2                   | Compensation principle I (CP I).....   | 14          |
| 5.2.3                   | Compensation principle II (CP II).....   | 14          |
| 5.2.4                   | Compensation principle III (CP III).....   | 14          |
| 5.2.5                   | Theoretical background.....  | 15          |
| <b>6</b>                | <b>General preparations and requirements</b> .....   | <b>15</b>   |
| 6.1                     | Protection against ionizing radiation.....   | 15          |
| 6.2                     | Surface preparation and stage of manufacture.....  | 15          |
| 6.3                     | Location of the weld in the radiograph.....  | 15          |
| 6.4                     | Identification of radiographs.....   | 15          |
| 6.5                     | Marking.....   | 15          |
| 6.6                     | Overlap of digital images.....   | 16          |
| 6.7                     | Types and positions of image quality indicators (IQIs).....  | 16          |
| 6.7.1                   | General.....   | 16          |
| 6.7.2                   | Duplex wire IQIs.....  | 16          |
| 6.7.3                   | Single wire or step-hole IQIs.....   | 16          |
| 6.8                     | Evaluation of image quality.....   | 17          |
| 6.9                     | Minimum image quality values.....  | 18          |
| 6.10                    | Personnel qualification.....   | 18          |
| <b>7</b>                | <b>Recommended techniques</b> .....  | <b>19</b>   |
| 7.1                     | Test arrangements.....   | 19          |
| 7.1.1                   | General.....   | 19          |
| 7.1.2                   | Single-wall penetration of plane objects (see <a href="#">Figure 1</a> ).....  | 20          |
| 7.1.3                   | Single-wall penetration of curved objects with the source outside the object (see <a href="#">Figures 2 to 4</a> ).....  | 20          |
| 7.1.4                   | Single-wall penetration of curved objects with the source inside the object for panoramic exposure (see <a href="#">Figures 5 to 7</a> ).....  | 21          |
| 7.1.5                   | Single-wall penetration of curved objects with the source located off-centre and inside the object (see <a href="#">Figures 8 to 10</a> ).....   | 22          |
| 7.1.6                   | Double-wall penetration and double-image evaluation (DWDI) of pipes with the elliptic technique and the source and the detector outside the object (see <a href="#">Figure 11</a> )..... | 23          |
| 7.1.7                   | Double-wall penetration and double-image evaluation (DWDI) with the perpendicular technique and source and detector outside the object (see <a href="#">Figure 12</a> ).....             | 23          |
| 7.1.8                   | Double-wall penetration and single-image evaluation (DWSI) of curved objects for evaluation of the wall next to the detector (see <a href="#">Figures 13 to 16</a> ).....                | 24          |

|                              |   |           |
|------------------------------|---|-----------|
| 7.1.9                        | Penetration of objects with different material thicknesses (see <a href="#">Figure 17</a> to <a href="#">19</a> ) | 25        |
| 7.2                          | Choice of tube voltage and radiation source   | 26        |
| 7.2.1                        | X-ray devices up to 1 000 kV  | 26        |
| 7.2.2                        | Other radiation sources   | 27        |
| 7.3                          | Detector systems and metal screens  | 28        |
| 7.3.1                        | Minimum normalized signal-to-noise ratio ( $SNR_N$ )  | 28        |
| 7.3.2                        | Compensation principle II   | 31        |
| 7.3.3                        | Metal screens for IPs and shielding   | 31        |
| 7.4                          | Alignment of beam   | 31        |
| 7.5                          | Reduction of scattered radiation  | 32        |
| 7.5.1                        | Metal filters and collimators   | 32        |
| 7.5.2                        | Interception of backscattered radiation   | 32        |
| 7.6                          | Source-to-object distance   | 32        |
| 7.7                          | Geometric magnification technique   | 39        |
| 7.8                          | Maximum area for a single exposure  | 40        |
| 7.9                          | Processing  | 40        |
| 7.9.1                        | Scan and read-out of images   | 40        |
| 7.9.2                        | Correction of acquired DDA images   | 41        |
| 7.9.3                        | Bad pixel interpolation   | 41        |
| 7.9.4                        | Image processing  | 41        |
| 7.10                         | Monitor viewing conditions and storage of digital radiographs   | 42        |
| <b>8</b>                     | <b>Test report</b>  | <b>42</b> |
| <b>Annex A</b> (normative)   | <b>Number of exposures for acceptable testing of a circumferential butt weld</b>                                  | <b>44</b> |
| <b>Annex B</b> (normative)   | <b>Minimum image quality values</b>   | <b>49</b> |
| <b>Annex C</b> (normative)   | <b>Determination of basic spatial resolution</b>  | <b>57</b> |
| <b>Annex D</b> (informative) | <b>Determination of minimum grey values for CR practice</b>   | <b>59</b> |
| <b>Annex E</b> (informative) | <b>Grey values — General remarks</b>  | <b>64</b> |
| <b>Annex F</b> (informative) | <b>Considering the detector unsharpness for <math>f_{min}</math></b>  | <b>66</b> |
| <b>Annex G</b> (informative) | <b>Calculation of recommended X-ray tube voltages from <a href="#">Figure 20</a></b>                              | <b>69</b> |
|                              | <b>Bibliography</b>   | <b>70</b> |