

# ISO 4664-1:2022-07 (E)

## Rubber, vulcanized or thermoplastic - Determination of dynamic properties - Part 1: General guidance

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>3.1</b>	<b>Terms applying to any periodic deformation .....</b>	<b>1</b>
<b>3.2</b>	<b>Terms applying to sinusoidal motion .....</b>	<b>3</b>
<b>3.3</b>	<b>Other terms applying to periodic motion .....</b>	<b>6</b>
<b>4</b>	<b>Symbols .....</b>	<b>6</b>
<b>5</b>	<b>General .....</b>	<b>8</b>
<b>5.1</b>	<b>Viscoelasticity .....</b>	<b>8</b>
<b>5.2</b>	<b>Use of dynamic test data .....</b>	<b>9</b>
<b>5.3</b>	<b>Classification of dynamic tests .....</b>	<b>9</b>
<b>5.3.1</b>	<b>General .....</b>	<b>9</b>
<b>5.3.2</b>	<b>Classification by type of vibration .....</b>	<b>9</b>
<b>5.3.3</b>	<b>Classification by mode of deformation .....</b>	<b>10</b>
<b>5.4</b>	<b>Factors affecting machine selection .....</b>	<b>11</b>
<b>6</b>	<b>Principles of dynamic motion for each vibration method .....</b>	<b>12</b>
<b>6.1</b>	<b>Forced vibration non-resonant method .....</b>	<b>12</b>
<b>6.1.1</b>	<b>Dynamic motion in linear response .....</b>	<b>12</b>
<b>6.1.2</b>	<b>Dynamic motion with nonlinear response .....</b>	<b>14</b>
<b>6.1.3</b>	<b>Free-vibration method .....</b>	<b>15</b>
<b>6.2</b>	<b>Forced resonant vibration .....</b>	<b>16</b>
<b>7</b>	<b>Test parameter dependence .....</b>	<b>18</b>
<b>7.1</b>	<b>Interdependence of frequency and temperature (time - temperature superposition) .....</b>	<b>18</b>
<b>7.2</b>	<b>Strain amplitude .....</b>	<b>19</b>
<b>8</b>	<b>Conditioning .....</b>	<b>19</b>
<b>8.1</b>	<b>Storage .....</b>	<b>19</b>
<b>8.2</b>	<b>Temperature .....</b>	<b>19</b>
<b>8.3</b>	<b>Mechanical conditioning .....</b>	<b>19</b>
<b>9</b>	<b>Forced vibration non-resonant method .....</b>	<b>20</b>
<b>9.1</b>	<b>Apparatus .....</b>	<b>20</b>
<b>9.2</b>	<b>Test piece .....</b>	<b>22</b>
<b>9.2.1</b>	<b>Test piece preparation .....</b>	<b>22</b>
<b>9.2.2</b>	<b>Test piece shapes and dimensions .....</b>	<b>22</b>
<b>9.2.3</b>	<b>Number of test pieces .....</b>	<b>24</b>
<b>9.3</b>	<b>Test conditions .....</b>	<b>24</b>
<b>9.3.1</b>	<b>Strain .....</b>	<b>24</b>
<b>9.3.2</b>	<b>Frequency and temperature .....</b>	<b>24</b>
<b>9.4</b>	<b>Test procedure .....</b>	<b>25</b>
<b>9.5</b>	<b>Expression of results .....</b>	<b>26</b>
<b>9.5.1</b>	<b>Parameters required .....</b>	<b>26</b>
<b>9.5.2</b>	<b>Wave-form method .....</b>	<b>26</b>

9.5.3	Hysteresis loop method .....	27
9.5.4	Stress-strain relationships and shape factors .....	28
10	Forced vibration resonant method .....	29
10.1	Apparatus .....	29
10.2	Expression of results .....	29
11	Free-vibration method .....	30
11.1	General .....	30
11.2	Test piece dimensions .....	30
11.3	Test conditions .....	30
Annex A (informative) Determination of the degree of nonlinearity(example of the calculation) .....		31
Annex B (informative) Procedure for time-temperature superposition(example of the calculation) ..		36
Bibliography .....		38