

ISO 24046:2022-08 (E)

Fine ceramics (advanced ceramics, advanced technical ceramics) - Methods of tests for reinforcements - Determination of the tensile properties of resin-impregnated yarns

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	3
5	Apparatus and material	3
5.1	Resin	3
5.2	Impregnation apparatus	3
5.3	Curing oven with temperature control	4
5.4	Tensile-testing machine and extensometer	4
5.4.1	Tensile-testing machine	4
5.4.2	Extensometer	4
5.5	Balance	4
5.6	Ruler	4
6	Test specimens	4
6.1	Number of test specimens	4
6.2	Impregnation of test specimens	4
6.3	Determination of other fibre properties	5
6.3.1	General	5
6.3.2	Linear density of the yarn	5
6.3.3	Size content of the yarn	5
6.3.4	Density of the ceramic fibre	5
6.4	Criteria for selection of the test specimens	5
6.4.1	Specimens	5
6.4.2	Resin content of the specimens	5
6.4.3	Impregnated yarn	6
7	Atmospheres for conditioning and testing	6
8	Procedure for tensile testing	6
8.1	Procedure	6
8.2	Determination of load train compliance	6
8.3	Test validity	6
9	Calculation of results	7
9.1	Tensile strength	7
9.2	Calculation of the load train compliance	7
9.3	Calculation of instantaneous total compliance and longitudinal deformation of resin-impregnated yarn	8
9.4	Tensile modulus of elasticity	9
9.5	Tensile strain at maximum force (percentage elongation at failure)	10

9.5.1	Calculation method (1)	10
9.5.2	Calculation method (2)	11
10	Statistics	11
11	Test report	11
Annex A (informative) Examples of heat-curable epoxy-resin systems		13
Annex B (informative) Examples of resin-impregnating apparatus		14
Annex C (informative) Example of extensometer		15
Bibliography		17